DATASHEET - IZMX-TF403-2500W-1

Connections, front, 2500A, IZMX40, 3 p, withdrawable

Part no.	**IZMX-TF403-2500W-1**
	184178
EL Number (Norway)	**4398521**

General specifications	
Product name	Eaton Moeller series IZMX/INX main terminal
Part no.	IZMX-TF403-2500W-1
EAN	4015081783502
Product Length/Depth	400 millimetre
Product height	200 millimetre
Product width	400 millimetre
Product weight	25.2 kilogram
Compliances	RoHS conform
Product Tradename	IZMX/INX
Product Type	Accessories
Product Sub Type	Main terminal
Delivery program	
Type	Accessory
Amperage Rating	2500 A - 3200 A
Special features	Each set includes the connections for top and bottom. 3-pole for 6 connections, 4-pole for 8 connections Screws, washers, and supports are included as standard. This connection kit comes with front terminals for connection to the cassette. The circuit breaker can be connected directly with CU bars on the rear flanged connection. If necessary, the optional front terminals can be installed before the circuit breaker is installed in the enclosure. This way, the final connection to the circuit breaker can be made from the front.
Suitable for	Three-pole
Used with	IZMX40…3…20W INX40…3…20W INX40…3…25W Three-pole IZMX40…3…25W
Technical Data - Mechanical	
Mounting Method	Withdrawable
Design verification as per IEC/EN 61439 - technical data	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Additional information	
Accessory/spare part type	Main terminal kits

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Connection vane/phase spreader (EC002019)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Connection vane/phase spreader (ecl@ss13-27-37-13-05 [ACN990017])

Suitable for number of poles	3

© 04/2023 by Eaton Industries GmbH