PRODUCT-DETAILS

UA26-30-10RA 24V 50Hz / 24V 60Hz

UA26-30-10RA 24V 50Hz / 24V 60Hz Contactor



General Information

Extended Product Type	UA26-30-10RA 24V 50Hz / 24V 60Hz
Product ID	1SBL241024R8110
EAN	3471522301819
Catalog Description	UA26-30-10RA 24V 50Hz / 24V 60Hz Contactor
Long Description	UA26..RA 3-pole contactors for capacitor switching, can be used in installations in which the peak current far exceeds 100 times nominal rms current. The contactors are delivered complete with their damping resistors and must be used without additional inductances (see table below). The capacitors must be discharged (maximum residual voltage at terminals ≤ 50 V) before being re-energized when the contactors are making. Their electrical durability is 250 000 operating cycles for Ue < 500 V and 100 000 operating cycles for 500 V ≤ Ue ≤ 690 V. The UA..RA contactors are fitted with a special front mounted block, which ensures the serial insertion of 3 damping resistors into the circuit to limit the current peak on energization of the capacitor bank. Their connection also ensures capacitor precharging in order to limit the second current peak occurring upon making of the main poles. The insertion of resistors allows to damp the highest current peak of the capacitor when switching on, whatever its level. The UA..RA series 3-pole contactors are of the block type design. - Main poles and auxiliary contacts: 3 main poles, 1 built-in auxiliary contact - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	1SBC101140C0203
Instructions and Manuals	1SBC101002M5501
Dimension Diagram	FPTE307846

Dimensions

Product Net Width	54 mm
Product Net Depth / Length	126.3 mm
Product Net Height	120 mm
Product Net Weight	0.71 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	0
Rated Operational Voltage	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Frequency (f)	Supply Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-5-1, q = 40 °C 16 A
Rated Operational Power AC-6b (P_e)	(230 / 240 V) 40 °C, 50 / 60 Hz 12.5 kvar (230 / 240 V) 55 °C, 50 / 60 Hz 11.5 kvar (230 / 240 V) 70 °C, 50 / 60 Hz 9 kvar (400 / 415 V) 40 °C, 50 / 60 Hz 22 kvar (400 / 415 V) 70 °C, 50 / 60 Hz 15.5 kvar (400 / 415 V) 55 °C, 50 / 60 Hz 20 kvar (440 V) 40 °C, 50 / 60 Hz 24 kvar (440 V) 55 °C, 50 / 60 Hz 20 kvar (440 V) 70 °C, 50 / 60 Hz 17 kvar (500 / 550 V), 40 °C, 50 / 60 Hz 30 kvar (500 / 550 V) 55 °C, 50 / 60 Hz 25 kvar (500 / 550 V) 70 °C, 50 / 60 Hz 20 kvar (690 V) 40 °C, 50 / 60 Hz 35 kvar (690 V) 55 °C, 50 / 60 Hz 31 kvar (690 V) 70 °C, 50 / 60 Hz 26 kvar
Rated Operational Current AC-15 (I_e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Short-Circuit Protective Devices	Auxiliary Circuit - gG Type Fuses 10 A gG Type Fuses 125 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for Ie > 100 A) at 440 V 420 A cos phi=0.45 (cos phi=0.35 for Ie > 100 A) at 690 V 170 A
Maximum Electrical Switching Frequency	240 cycles per hour
Rated Operational Current	(24 V) 6 / 144 A

DC-13 (I_e)	(48 V) 2.8 / 134 A (72 V) 2 / 144 A (125 V) 1.1 / 138 A (250 V) 0.55 / 138 A
Rated Insulation Voltage (U_i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Control Circuit Voltage (U_c)	50 Hz 24 V 60 Hz 24 V
Coil Consumption	Average Holding Value 50 / 60 Hz 12 V·A Average Holding Value 50 Hz 12 V·A Average Holding Value 60 Hz 12 V·A Average Pull-in Value 50 Hz 120 V·A Average Pull-in Value 60 Hz 140 V·A
Operate Time	Between Coil De-energization and NO Contact Opening 4 ... 11 ms Between Coil Energization and NO Contact Closing 8 ... 21 ms
Connecting Capacity Auxiliary Circuit	Flexible with Cable End 0.75 ... 2.5 mm² Rigid Cable 1 ... 4 mm²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20
Connecting Terminals (delivered in open position) Main Poles	M 4 (+,-) pozidriv 2 screws with cable clamp
Terminal Type	Screw Terminals

Environmental

Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 °C Near Contactor for Operation in Free Air (0.85 ... 1.1 Uc) -40 ... +55 °C Near Contactor for Operation in Free Air (Uc) -40 ... +70 °C
Climatic Withstand	acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II
Maximum Operating Altitude Permissible	3000 m
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

CB Certificate	CB_FR3447_60016915-509739B
CCC Certificate	CCC_2004010304138316
CQC Certificate	CQC2003010304060095 CQC2008010304261926
CSA Certificate	CSA_1033838_LR056745
Declaration of Conformity - CCC	2020980304001610 2020980304001217
Declaration of Conformity - CE	1SBD250805U1000
Environmental Information	1SBD250123E1000
GOST Certificate	GOST_POCCFRME77B07175
Instructions and Manuals	1SBC101002M5501
RoHS Information	1SBD250805U1000

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	135 mm
Package Level 1 Depth / Length	155 mm
Package Level 1 Height	63 mm
Package Level 1 Gross Weight	0.71 kg
Package Level 1 EAN	3471522301819
Package Level 2 Units	box 63 piece
Package Level 2 Gross Weight	44.73 kg

Classifications

Object Classification Code	Q
ETIM 4	EC001079 - Capacitor magnet contactor
ETIM 5	EC001079 - Capacitor magnet contactor
ETIM 6	EC001079 - Capacitor contactor
ETIM 7	EC001079 - Capacitor contactor
eClass	V11.0 : 27371006
UNSPSC	39121529

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → UA and UA..RA Contactors

