Specifications

Eaton C14M6S



Catalog Number: C14M6S

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 6 Amps, 120 kA Breaking capacity, class aM, with striker, compatible with a CH14 Modular fuse holder

General specifications

Product Name
Eaton Bussmann series low voltage cylindrical fuse

Catalog Number
C14M6S

EAN
5027590495004

UPC
051712666640

Product Length/Depth
51 mm

Product Height
14 mm

Product Width
14 mm

Product Weight
19.9 g

Compliances
RoHS Compliant
CE Marked

Certifications
IEC 60269

Powering Business Worldwide

Electrical data

Amperage Rating

6 A

Voltage rating

500 V

Voltage type

AC

Breaking capacity

120 kA

Utilization category

aM (switchgear protection)

Frequency rating - max

62 Hz

Compatible fuse holder

Suitable for

CH14 Modular fuse holder

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

CA134002EN

Declarations of conformity

CE C08G, C08M, etc cylindrical fuselinks

UKCA C08G, C08M, etc cylindrical fuselinks

Technical data sheets

720115 Cylindrical fuses

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia