CAT. N° 0 489 35



DALI LIGHTING MANAGEMENT SENSOR - 360° IR AND ULTRASONIC - RANGE Ø 8 M

Pack (number of units)	1
Volume (dm³)	1,563
Weight (g)	181,00

Product characteristics

DALI lighting management sensors

- Check presence and light level continuously, switch off when there is sufficient natural light
- Manual switch-on and manual or automatic switch-off (factory setting)
- Configuration tool Cat.No 0 882 30

Version for work areas

- Suitable for meeting rooms, classrooms, open plan areas, etc.
- 360° infrared and ultrasonic detection, range Ø8 m
- IP 20
- Optimum distance between 2 sensors: 6 m
- Fixed directly to the suspended ceiling with mounting claws (supplied) or installed in 50mm deep Batibox boxes
- Connection by automatic terminals
- Surface mounted on ceiling using accessory Cat.No 0 488 75
- With 1 RJ 45 input
- Supplied with RJ 45/BUS connector 16 V – 30 mA

General characteristics

DALI management - for 1 or 2 circuits

Documentation

Catalogue pages & additional information

- Description page (p.668)
- Lighting management stand-alone sensors

Installation & technical data

- S000088482EN-1

Installation instructions & related documents

- LE08324AA

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.