

Inductive Sensors





Housing Style	Part Number	ID Number	Features	Sensing Range (mm)	Output
12 mm - Embeddable, *eurofast*® Connection 	Bi 4-M12K-AN6X-H1141	T4607101	*Short Barrel*	4	3-Wire DC PNP
	Bi 4-M12K-AP6X-H1141	T4607082	*Short Barrel*	4	3-Wire DC PNP
	Bi 2-M12K-VP6X-H1141	M1633005	*Short Barrel*	2	4-Wire DC PNP
12 mm - Embeddable, *eurofast* Connection 	Bi 2-M12-AD4X-H1141	T4406500		2	2-Wire DC
	Bi 3-M12-AD4X-H1141	T4405041	*Ext. Range*	3	
	Bi 2-EM12-AN6X-H1141	T4606601		2	3-Wire DC NPN
	Bi 2-M12-AN6X-H1141	T4606600		2	
	Bi 3-EM12WD-AN6X-H1141	M1634334	*Washdown*	3	
	Bi 3-M12WD-AN6X-H1141	M4607120	*Washdown*	3	
	Bi 3U-EM12-AN6X-H1141	M1634350	*Uprox*	3	
	Bi 3U-M12-AN6X-H1141	M1634150	*Uprox*	3	
	Bi 3U-M12-AN6X2-H1141	M1634155	*Uprox*	3	
	Bi 4-M12-AN6X-H1141	T4607100	*Extended Range*	4	
	Bi 2-EM12-AP6X-H1141	T4606501		2	3-Wire DC PNP
	Bi 2-M12-AP6X-H1141	T4606500		2	
	Bi 3-EM12WD-AP6X-H1141	M1634331	*Washdown*	3	
	Bi 3-M12WD-AP6X-H1141	M4607121	*Washdown*	3	
	Bi 3U-EM12-AP6X-H1141	M1634340	*Uprox*	3	
	Bi 3U-EM12H-AP6X-H1141	M1634312	*Uprox, Stoneface*	3	
	Bi 3U-M12-AP6X-H1141	M1634140	*Uprox*	3	
	Bi 3U-M12-AP6X2-H1141	M1634145	*Uprox*	3	
	Bi 4-M12-AP6X-H1141	T4607000	*Extended Range*	4	
	Bi 2-M12-VN6X-H1141	T1643000	*Comp. Outputs*	2	4-Wire DC NPN
	Bi 4-M12-VN6X-H1141	T1643200	*Ext. Range, Comp. Outputs*	4	
	Bi 2-M12-VP6X-H1141	T1633000	*Comp. Outputs*	2	4-Wire DC PNP
	Bi 4-M12-VP6X-H1141	T1633200	*Ext. Range, Comp. Outputs*	4	
	Bi 4-EM12-VP6X-H1141	T1633201	*Ext. Range, Comp. Outputs*	4	
	Bi 2-EM12-YOX-H1141	T4010098		2	2-Wire DC NAMUR
	Bi 2-M12-Y1X-H1141	M4010200		2	

Industrial Automation

TURCK Industrial Automation

Voltage	Switching Freq. (Hz)	Operating Current (mA)	Operating Temp. (°C)	Protection	Housing	Face	Power LED	Output LED	Mating Cordset	Wiring Diagram #
10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	2
10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	3
10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	5
10-65 VDC	1000	≤100	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.2T-*	1
	1000	≤100	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.2T-*	1
10-30 VDC	2000	≤200	-25 to +70	IP 67	SS	PA 12	N/A	YE	RKV 4T-*	2
	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	2
	2000	≤200	-25 to +85	IP 68, 69K	SS	PVDF	N/A	YE	RK 4T-*	2
	3000	≤200	-25 to +85	IP 68, 69K	SS	PVDF	N/A	YE	RK 4T-*	2
	3000	≤200	-30 to +85	IP 68	SS	PA 12	N/A	YE	RKV 4T-*	2
	3000	≤200	-30 to +85	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	2
	3000	≤200	-30 to +85	IP 67	CPB	PA 12	GN	YE	RK 4T-*	2
	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	2
10-30 VDC	2000	≤200	-25 to +70	IP 67	SS	PA 12	N/A	YE	RKV 4T-*	3
	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	3
	2000	≤200	-25 to +85	IP 68, 69K	SS	PVDF	N/A	YE	RK 4T-*	3
	3000	≤200	-25 to +85	IP 68, 69K	SS	PVDF	N/A	YE	RK 4T-*	3
	3000	≤200	-30 to +85	IP 68	SS	PA 12	N/A	YE	RKV 4T-*	3
	3000	≤200	-30 to +85	IP 68	SS	SF	N/A	YE	RKG 4T-*/S600	3
	3000	≤200	-30 to +85	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	3
	3000	≤200	-30 to +85	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	3
	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	3
10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	4
	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	4
10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	5
	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	5
	2000	≤200	-25 to +70	IP 67	SS	PA 12	N/A	YE	RKV 4.4T-*	5
5-30 VDC	5000	Remote	-25 to +70	IP 67	SS	PA 12	N/A	YE	RKV 4.21T-*	6
	5000	Remote	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.21T-*	6

Wiring Diagrams

Diagram 1




Diagram 2




Diagram 3




Diagram 4




Diagram 5





Diagram 6




* Length in meters.

WIRING DIAGRAM




SHORT-CIRCUIT AND OVERLOAD PROTECTED

LOCKNUT LN-M12



SPECIFICATIONS	
OPERATING VOLTAGE	10-30 VDC
RIPPLE	≤ 10%
DIFFERENTIAL TRAVEL (HYSTERESIS)	3-15% (5% TYPICAL)
VOLTAGE DROP ACROSS CONDUCTING SENSOR	≤ 1.8 V at 200 mA
OUTPUT FUNCTION	NORMALLY OPEN 3-WIRE DC SELF-CONTAINED
TTL COMPATIBLE	NO
SHORT-CIRCUIT PROTECTED	YES
TRIGGER CURRENT FOR OVERLOAD PROTECTION	≥ 220 mA
CONTINUOUS LOAD CURRENT	≤ 200 mA
OFF-STATE (LEAKAGE) CURRENT	≤ 0.1 mA
NO-LOAD CURRENT	≤ 8 mA
TIME DELAY BEFORE AVAILABILITY	≤ 6 ms
POWER-ON EFFECT	PER IEC 947-5-2
REVERSE POLARITY PROTECTION	INCORPORATED
WIRE-BREAK PROTECTION	INCORPORATED
PROTECTION AGAINST TRANSIENTS	Per EN 60947-5-2
OPERATING TEMPERATURE (10% DRIFT)	-25°C to +70°C (-13°F to +158°F)
ENCLOSURE	MEETS NEMA 1, 3, 4, 6, 13 AND IEC IP67
SHOCK	30 g, 11 ms
VIBRATION	55 Hz, 1 mm AMPLITUDE (IN ALL 3 PLANES)
LED FUNCTION	YELLOW: OUTPUT ENERGIZED
RATED OPERATING DISTANCE(Sn)	4 mm = .158" (NOMINAL)
SWITCHING FREQUENCY	2000 Hz
REPEATABILITY	≤ 2% of RATED OPERATING DISTANCE
EMBEDDABLE (SHIELDED)	YES
MATING PLUGS/CABLES	4-PIN "EUROFAST® CONSTRUCTION



RELATED DOCUMENTS
1.
2.
3.
4.

3RD ANGLE PROJECTION

THIS DRAWING IS PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

TURCK INC
High Technology Sensors and Automation Controls

MATERIAL: BRASS BARREL

FINISH: COPPER, NICKEL, CHROME PLATING

TOLERANCES UNLESS OTHERWISE SPECIFIED: 0.0394in [1.00mm]

DRT: GMB | DATE: 09/28/99
DSGN: | SCALE: NONE

UNIT OF MEASUREMENT: INCH [MILLIMETER]
DO NOT SCALE THIS DRAWING

DESCRIPTION: BI 4-M12-AP6X-H1141

IDENTIFICATION NO.: T4607000 | REV: B

FILE: T4607000 | SHEET 1 OF 1

REV.	DESCRIPTION	BY	DATE	ECO NO.
B	UPDATE SENSOR GEOMETRY	CHM	09/28/99	T2905