# Flashguard LED Beacons

Flashguard weatherproof LED beacons are ideal visual indicators in a variety of applications.

All Flashguard beacons are fitted with a diffuser for greater visibility and spread of light. Two styles are available. Standard and Ultra Low Profile.

**Standard:** includes a terminal block and a 27mm deep base supplied with a seal and grommet.

**Ultra Low Profile:** comes complete with a screw and nylon wing nut and is supplied with mounting gasket and 40cm of cable.

A weatherproof cable connector is available to upgrade the product from IP65 rating to IP67.

## Features

- **Compact, ultra modern sleek appearance**
- **Long life LED design**
- **Ease of installation with first-fix option on standard models**
- **Weatherproof to IP67 (with cable connector)**
- **White, high quality polycarbonate housing**
- **Vandal-resistant safety locking mechanism**
- **Flashing or static indicators**

## Colour Options





**Applications -** Fire alarm; security alert; emergency warning; process control alarm

Standard and Fire Style




Ultra Low Profile Style




- Fire
- Security
- Industrial
- Railway/Marine
- Hazardous Area
- Public Warning

## Specifications

| Type and Style | Part No. Red Lens | Part No. Amber Lens | Part No. Clear Lens | Part No. Blue Lens | Part No. Green Lens | Voltage | Current | Static or Flashing | Flash Rate |
|---|---|---|---|---|---|---|---|---|---|
| LED Standard | 45-711611 | 45-711621 | 45-711631 | 45-711641 | 45-711651 | 110V AC | 32mA | Static | N/A |
| LED Standard | 45-711811 | 45-711821 | 45-711831 | 45-711841 | 45-711851 | 110V AC | 32mA | Flashing | 1Hz |
| LED Standard | 45-712611 | 45-712621 | 45-712631 | 45-712641 | 45-712651 | 230V AC | 32mA | Static | N/A |
| LED Standard | 45-712811 | 45-712821 | 45-712831 | 45-712841 | 45-712851 | 230V AC | 32mA | Flashing | 1Hz |
| LED Standard | 45-716411 | 45-716421 | 45-716431 | 45-716441 | 45-716451 | 11/35V DC | 50mA** | Static/Flashing* | 1Hz |
| LED Ultra Low Profile | 45-716413 | 45-716423 | 45-716433 | 45-716443 | 45-716453 | 11/35V DC | 50mA** | Static/Flashing* | 1Hz |

*These units are user-configurable
**Clear, blue and green versions draw upto 100mA

**IP Rating:** IP65 (Standard) IP67 (Ultra) **Operating Temp:** -20ºC to +70ºC
**Construction:** UV Stabilised Polycarbonate **Weight:** 0.14kg