





TOP VIEW




SECTION A-A
END VIEW





SECTION B-B
SIDE VIEW




DETAIL C


Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
Contact Factory mjm@hammondmfg.com for quotes
Solid models of this enclosure available in STEP or IGES.
(Part number and text placement/orientation on our products are subject to change, we do not recommend using them as a locating reference for modification purposes)

NOTE
Purchased assembly includes box, lid and 4 cover screws.
Box and lid are made from Diecast Aluminum Alloy.
Silicone Gasket supplied with liquid resistant enclosure.
Bottom Flange is Welded.
Recommended Torque: 50-55 cN.m [71-78 ozf.in]
Recommended Torque with Gasket : 25-30 cN.m [36-43 ozf.in]

PART NUMBERS	
1590PF Enclosure	
Natural Finish Enclosure	1590PF
Black Textured Enclosure	1590PFBK
1590PF Liquid Resistant Enclosure (Silicone Gasket)	
Natural Finish Enclosure	1590WPF
Black Textured Enclosure	1590WPFBK
ACCESSORIES	
Liquid Resistant Cover Screws	
Stainless Steel Cover Screws (Pkg 100) [M3.5 x 12mm, With O-Ring]	1550WMS100
Black Stainless Steel Cover Screws (Pkg 100) [M3.5 x 12mm, With O-Ring]	1550WMS100BK
Standard Cover Screws	
Plated Cover Screws (Pkg 100) [M3.5 x 12mm]	1550MS100
Black Cover Screws (Pkg 100) [M3.5 x 12mm]	1550MS100BK



INSIDE LID



INSIDE BOX

Dimensions:
mm
[inches]

HAMMOND MANUFACTURING®

1590PF

www.hammondmfg.com