Housemaster

Consumer Units





HMSL8+8

Moulded Enclosure to BS EN 60439-3

- Supplied factory fitted with switch disconnector and/or RCD, specification as table. Unit comes complete with blanking plates, busbar, busbar cover, terminal bars and installation instructions.
- Colour RAL 9010 white

	Incomer		Split Load			
Ways	Switch Disconnector	Switch RCD	Disconnector	RCD	Order Code	Price £
4	100A				HMMS4	
4		100A/30mA			HMRC4	
6	100A				HMMS6	
6		100A/30mA			HMRC6	
10	100A				HMMS10	
10		100A/30mA			HMRC10	
4 + 4			100A	80A/30mA	HMSL4+4	
14	100A				HMMS14	
14		100A/30mA			HMRC14	
6+6			100A	80A/30mA	HMSL6+6	
18	100A				HMMS18	
18		100A/30mA			HMRC18	
8+8			100A	80A/30mA	HMSL8+8	

Housemaster Consumer Unit



HSSL8+8

Steel Enclosure to BS EN 60439-3

- Supplied factory fitted with switch disconnector and/or RCD, specification as table. Unit comes complete with busbar, busbar cover, and terminal bars.
- Colour RAL7035 Grey

	Incomer		Split Load			
Ways	Switch Disconnector	Switch RCD	Disconnector	RCD	Order Code	Price £
4	100A				HSMS4	
4		100A/30mA			HSRC4	
7	100A				HSMS7	
7		100A/30mA			HSRC7	
10	100A				HSMS10	
10		100A/30mA			HSRC10	
4 + 4			100A	80A/30mA	HSSL4+4	
16	100A				HSMS16	
16		100A/30mA			HSRC16	
6+6			100A	80A/30mA	HSSL6+6	
20	100A				HSMS20	
20		100A/30mA			HSRC20	
8+8			100A	80A/30mA	HSSL8+8	



S261

MCBs - single pole - BS EN 60898

Current Rating Amps	Breaking Capacity kA	Outgoing Cable Capacity	Type B Order Code	Type C Order Code	Price £
6	6	25mm²	S261B6	S261C6	
10	6	25mm²	S261B10	S261C10	
13	6	25mm²	S261B13	S261C13	
16	6	25mm²	S261B16	S261C16	
20	6	25mm²	S261B20	S261C20	
25	6	25mm²	S261B25	S261C25	
32	6	25mm²	S261B32	S261C32	
40	6	25mm²	S261B40	S261C40	
50	6	35mm²	S261B50	S261C50	
63	6	35mm²	S261B63	S261C63	

Type B - Suitable for small inrush or switching surges, heating loads and tungsten lighting
Type C - Suitable for moderate switching surges for short duration. eg. discharge lamps.

RCBO single module, solid neutral to BS EN 61009



DS271AC-C6/0.03

- Supplied with 800mm flying neutral & functional earth leads

Current Rating Amps	Breaking Capacity kA	Outgoing Tripping mA	Cable Capacity	Type B Order Code	Type C Order Code	Price £
6	10	30mA	10mm²	DS271AC-B6/0.03	DS271AC-C6/0.03	
10	10	30mA	10mm²	DS271AC-B10/0.03	DS271AC-C10/0.03	
16	10	30mA	10mm²	DS271AC-B16/0.03	DS271AC-C16/0.03	
20	10	30mA	10mm²	DS271AC-B20/0.03	DS271AC-C20/0.03	
25	10	30mA	10mm²	DS271AC-B25/0.03	DS271AC-C25/0.03	
32	10	30mA	10mm²	DS271AC-B32/0.03	DS271AC-C32/0.03	

Accessories



SA1



SA2

Type	Order Code	Price £
MCB padlock adaptor 3mm hasp	SA1	
Padlock with 2 keys	SA2	
Moulded Housemaster connection bridge	HMCB	
Moulded Housemaster spare blanking piece 4 modules	HMBS	
Moulded Housemaster spare profile clip 4 modules	HMPC	
Steel Housemaster blanking cover 213mm long (plastic)	SZ-BP1	
Steel Housemaster blanking piece 1 module (plastic)	SZ-BP2	