

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.


REVISIONS

REV	DESCRIPTION	DATE	CHANGED BY
B	RELEASED FOR PRODUCTION	11/19/01	MCCORMICK
B	REVISED TOLERANCES PER ECN 1489	08/08/03	MCCORMICK
C	ECN 3131: UPDATE DWG FORMAT	12/28/07	D.GRIFFIN



2X BNC JACK





BNC PLUG

SPECIFICATIONS;

MATERIALS;
SHELL: BRASS
INSULATOR: DELRIN

FINISH;
SHELL: NICKEL PLATED
CONTACT: GOLD PLATED

ELECTRICAL;
CHARACTERISTIC IMPEDANCE: 50 OHM

RoHS Compliant ✔

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm]
TOLERANCES TO BE:
.X ±.1 [2.5] ANGLES ±2°
.XX ±.01 [.25]
.XXX ±.005 [.13]
OVERALL CABLE LENGTH TOL:
≤ 60 [1524] +3 [76.2] / - 0
> 60 [1524] +5% / -0%

PROJ

APPROVALS	DATE
DRAWN BY MCCORMICK	11/14/01
CHECKED BY D.PARHAM	11/14/01
APPROVED BY R.CARRICK	11/12/01

CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY

L-com CONNECTIVITY PRODUCTS
45 BEECHWOOD DRIVE
NORTH ANDOVER, MA
01845

CATEGORY: COAXIAL

PRODUCT DESCRIPTION: Y ADAPTOR BNC M/F/F

SIZE	FSCM NO.	DWG. NO.	REV.
A	43321	BA845	C

SCALE: NONE | CAD FILE: BA845.SLDDRW | SHEET 1 OF 1