5-Pin Mini-Style Cordsets with Shield and "Twisted Pair"

Cable: PVC jacket, PUR (polyurethane) connector body, nickel-plated brass coupling nut
Conductors: 20 AWG (shielded), PVC insulation, gold-plated contacts
Voltage Rating: 250V ac/300V dc
Temperature: -40° to +90° C **Environmental Rating:** IP67

Style	Length	Model	Cable Diameter	Dimensions (mm)	Pinout	Used With
Straight	4.57 m	QDC-515C	7.00 mm		Female  1 = Black 2 = Blue 3 = Drain 4 = Brown 5 = White	• MINI-ARRAY • High-Resolution MINI-ARRAY
	7.62 m	QDC-525C				
	15.2 m	QDC-550C				
	22.9 m	MAQDC-575C				
	30.5 m	MAQDC-5100C				
	38.1 m	MAQDC-5125C				
	45.7 m	MAQDC-5150C				

8-Pin Mini-Style Cordsets

Cable: PVC jacket, PUR (polyurethane) connector body, nylon coupling nut
Conductors: 20 AWG, PVC insulation, gold-plated contacts
Voltage Rating: 250V ac/300V dc
Temperature: -40° to +80° C **Environmental Rating:** IP67

Style	Length	Model	Cable Diameter	Dimensions (mm)	Pinout	Used With
Straight	4.51 m	QDS-815C	6.90 mm		Female  1 = Brown 2 = Or/Bk 3 = Orange 4 = White 5 = Black 6 = Blue 7 = Gn/Ye 8 = Violet	• EZ-SCREEN Receivers w/8-pin QD (Point & Grid) • DUO-TOUCH SG Run Bar
	7.62 m	QDS-825C				
	15.2 m	QDS-850C				
	22.9 m	QDS-875C				

BNC Coaxial Video Cordsets

Style	Length	Model	Cable Diameter	Dimensions (mm)	Pinout	Used With
Video Coaxial with BNC	1.83 m	BNC06	6.00 mm		Male 	• *Pro* • *P4*
	4.57 m	BNC15				
	9.14 m	BNC30				
	14.6 m	BNC48				