Date: 12/04/2023

FSD-4; m/s; 65 mm; G1/2 A ISO1179-2; two switching outputs (PNP/NPN)

Specifications according to data sheet: FL 80.02

Item number:	14492161	
Quantity:	1 pcs.	
Order code:	FSD-4-9Z-14C0025-1GN15-WWZ-ZZZ	W1011FS4Z-2HOSGSEW
Overview:	FSD-4; m/s; 65 mm; G1/2 A ISO1179-2; two switching outputs (PNP/NPN) Output signal: two switching outputs (PNP/NPN) IO-Link: without Power supply: 15 ... 35 V DC Unit, display: m/s Unit: °C Probe length: 65 mm Process connection: G1/2 A ISO1179-2 Sealing: NBR Accessories process connection: without Electrical connection: circular connector M12x1, 4-pin Approvals: cULus Configuration flow switch: Factory setting acc. to manual Additional ordering information: without Specifications according to data sheet: FL 80.02	
Details:	Specifications according to data sheet: FL 80.02 Output signal: two switching outputs (PNP/NPN) IO-Link: without Unit, display: m/s Unit: °C Pipe Diameter: 25 mm Process connection: G1/2 A ISO1179-2 Sealing: NBR Probe length: 65 mm Approvals: cULus Configuration flow switch: Factory setting acc. to manual Certificates: without Accessories process connection: without Additional ordering information: without customer-name begins with: W1 (Wika standard) Customer logo: WIKA standard Customer address: www.wika.com Permissible medium temperature: -20 ... +85°C Model name customer-specific: FSD-4 Test protocol: without test protocol Type of packaging: twist pack Import documentation CIS-States: without	

© 2023 - WIKA Instruments s.a.r.l.

label: country of origin: *Made in Germany* on label
Customer-specific: WIKA standard - specification according to data sheet
Model: FSD-4

© 2023 - WIKA Instruments s.a.r.l.