Rittal – The System.

Faster – better – everywhere.

Socket strip in a plastic housing – DK 7000.630

Date : Apr 26, 2021

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Socket strip in a plastic housing – DK 7000.630

created: 26.04.2021 build on www.rittal.com/uk-en



Product description

Description:	8-way socket strip for earthing-pin plug (type F, CEE 7/4) The strip may be mounted vertically on the enclosure frame or in the rear 482.6 mm (19") section. In the 482.6 mm (19") section, more than 2 U of space is required. The sockets are arranged at an angle of 45° so that angular connectors are also easily used. The connection cable is contacted in a terminal slot in the strip. The terminal slot has a separate cover and external terminals for separate earthing.
Material:	Plastic
Supply includes:	Connection cable Assembly screws 2 serrated washers Captive nuts M6, conductive Nuts

Product description

Design:	Without switch
Installation options:	TE 7000, rear 482.6 mm (19") section (> 2 U) TE 7000, vertically mounted on the frame
Type of electrical connection:	Wire end ferrules
Rated voltage:	230 V AC
Rated current (max.):	16 A
Equipment (electrical):	Number of sockets: 8 Jack/socket (type): D, earthing-pin (type F, CEE 7/3) No. of sockets and type: 8 x earthing-pin, type F, CEE 7/3

	Colour of socket: Black Length of connection cable: 2 m
Connection cable (type):	H05VV-F3G1.5 with wire end ferrules
Packs of:	1 pc(s).
Weight/pack:	0.92 kg
Copper weight (kg per piece):	0
EAN:	4028177438569
Customs tariff number:	85369095
ETIM 7.0:	EC000330
ETIM 6.0:	EC000330
eCl@ss 8.0/8.1:	27142604
eCl@ss 6.0/6.1:	27142604
Product description:	DK-TS Socket strip, CEE 7/3 (type F), 8-way, 230 V, 16 A, LHD:

Approvals

Certificates:	EAC
Declarations:	Declaration of conformity