efectorsoo

PU5414

PU-016-SEG14-B-DVG/US/ /W

Pressure sensors



1: sealing FKM / DIN 3869

Made in Germany

Product characteristics		
Electronic pressure sensor		
for industrial applications		
Process connection: G ¼ A (according to DIN EN ISO 1179-2)		
Analogue output		
Measuring range: 0...16 bar		
Application		
Application		Type of pressure: relative pressure liquids and gases of the fluid group 2 according to Article 9 of the Pressure Equipment Directive (PED)
Pressure rating	[bar]	40 (static)
Bursting pressure min.	[bar]	450
Medium temperature	[°C]	-40...90
Electrical data		
Electrical design		DC
Operating voltage	[V]	16...36 DC
Current consumption	[mA]	< 12
Insulation resistance	[MΩ]	> 100 (500 V DC)
Protection class		III
Reverse polarity protection		yes
Outputs		
Output		Analogue output
Output function		0...10 V analogue
Short-circuit proof		yes
Overload protection		yes
Min. Lastwiderstand	[Ω]	2000
Measuring / setting range		
Measuring range	[bar]	0...16
Accuracy / deviations		
Accuracy / deviations (in % of the span)		
Characteristics deviation *)		< ± 0.5
Linearity		< ± 0.1 (BFSL) / < ± 0.2 (LS)
Hysteresis		< ± 0.2
Repeatability **)		< ± 0.05
Long-term stability ***)		< ± 0.1

efectorsoo

PU5414

PU-016-SEG14-B-DVG/US/ /W

Pressure sensors

Temperature coefficients (TEMPCO) in the temperature range -40...90° C (in % of the span per 10 K)

Greatest TEMPCO of the zero point + span		< ± 0.1 (-25...90 °C) / < ± 0.2 (-40...-25 °C)

Reaction times

Step response time analogue output	[ms]	1

Environment

Ambient temperature	[°C]	-40...90
Storage temperature	[°C]	-40...100
Protection		IP 67 / IP 69K

Tests / approvals

EC pressure equipment directive 97/23/EC		Article 3, section 3 - sound engineering practice
EMC		DIN EN 61000-6-2 DIN EN 61000-6-3
Shock resistance		DIN EN 60068-2-27: 50 g (11 ms)
Vibration resistance		DIN EN 60068-2-6: 20 g (10...2000 Hz)
MTTF	[Years]	1142.7

Mechanical data

Process connection		G ¼ A (according to DIN EN ISO 1179-2)
Materials (wetted parts)		1.4542
Housing materials		stainless steel 316L / 1.4404; PA
Min. pressure cycles		60 millions in the course of the lifetime (at 1.2 times the nominal pressure)
Tightening torque	[Nm]	25...35 (recommended tightening torque[1])
Weight	[kg]	0.055

Electrical connection

Connection		M12 connector

Wiring

Core colours

BN brown

BU blue

WH white





OUT: Analogue output

Colours to DIN 47100

Remarks

Remarks	*) incl. drift when overtightened, zero point and span error, non-linearity, hysteresis **) with temperature fluctuations < 10 K ***) in% of the span / 6 months [1]) Depends on lubrication, seal and pressure rating BFSL = Best Fit Straight Line / LS = Limit Value Setting
Pack quantity [piece]	1