Date: 11/04/2023

TR33, 4...20mA, G1/4 fixed, 75 mm x 6 mm

TR33 Miniature resistance thermometer, thread-mounted

Item number: 48788440

Quantity: 1 pcs.

Order code: TR33-Z-TT-CL1100-1160075-ZZZ-FZZ-CZZ R33 0086CW0000WIKA0Z CERT31-EG3E-AC- - - - - - - - - - - TE-CT1

Overview: TR33, 4...20mA, G1/4 fixed, 75 mm x 6 mm

Output signal: 4...20mA -10°C 100°C
Electrical connection: Circular connector, M12x1

Process connection: Fixed threaded hex bushing G1/4 B
Process temperature: -30 ... +150°C
Sensor diameter ød: 6 mm
Insertion length A: 75 mm
Permissible ambient temperature: -40 ... +85 °C (-40 ... +185 °F)
Pin assignment: 1+ (10..30VDC) und 3- (0V)

Specifications according to data sheet: TE 60.33

Inspection certificate acc. to DIN EN 10204 3.1
Certificate Language: English and German
Electrical thermometer with thermowell, with transmitter
Accuracy: 2 test points (0°C / 100° C) for RTD

Details: TR33 Miniature resistance thermometer, thread-mounted
Specifications according to data sheet: TE 60.33
Electrical connection: Circular connector, M12x1
Output signal: 4…20mA, 2-wire
Transmitter Unit: °C
Process temperature: -30 ... +150°C
Transmitter initial value: -10°C
Transmitter final value: 100°C
Process connection: Fixed threaded hex bushing G1/4 B
Sensor diameter ød: 6 mm
Insertion length A: 75 mm
Permissible ambient temperature: -40 ... +85 °C (-40 ... +185 °F)
Pin assignment: Standard pin connection 1+ (10..30VDC) and 3- (0V)
Inspection certificate acc. to DIN EN 10204 3.1
Certificate Language: English and German
Electrical thermometer with thermowell, with transmitter
Accuracy: 2 test points (0°C / 100° C) for RTD

Despatch date: 20/04/2023

© 2023 - WIKA Instruments s.a.r.l.