by Honeywell

**Technical Specifications**

# TURBOLITE

**Description:**

2 m Self retracting webbing lifeline. The first affordable alternative to shock-absorbing lanyards used in fall factor 2. Adapted to all situations when working with low space clearance. Can be used on both ways around.



**References**:

1018015 Twistlock karabiner x 2
1018013 Twistlock karabiner + Scaff Hook
1018014 Scaff Hook + Twistlock karabiner
1017900 Twistlock karabiner + Snap Hook
1034240 Twist lock karabiner alu + swivel scaff hook alu.

NEW !

**Features:**

Housing: Impact resistant nylon
Braking System: stainless steel
Webbing: Vectran (25.4mm x 1.5mm)
Length of the srl : 2 m
Shock Absorber maxi length when full deployed 60 cm
Max. rated Load :136 kg (use in up anchorage point)

100 kg (use in down level)

EN 360

HONEYWELL FALL PROTECTION FRANCE SAS
35-37 rue de la Bidauderie
F - 18100 Vierzon - France
Tel : +33 2 48 52 40 40
Fax : +33 2 48 71 04 97
Web site : www.honeywellsafety.com

| Ref | 1018015 | 1018013 | 1018014 | 1017900 | 1034240 |
|---|---|---|---|---|---|
| **Length** | 2 m | 2 m | 2 m | 2 m | 2 m |
| **Anchorage connection** | Twist lock karabiner opening 18mm | Twist lock karabiner opening 18mm | Scaff Hook Opening 65mm | Twist lock karabiner opening 18mm | Twist lock karabiner opening 18 mm |
| |  |  |  |  |  NEW ! |
| **Harness connection** | Twistllock karabiner opening 18mm | Scaff Hook Opening 65mm | Twistllock karabiner opening 18mm | Snap Hook Opening 21mm | Swivel scaff hook Opening 60 mm |
| **Weight** | 0,877 kg | 1,252 kg | 1,252 kg | 0.860 kg | 1,015 kg |

***LAW of 19 MARCH 93***

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS
35-37 rue de la Bidauderie
F - 18100 Vierzon - France
Tel : +33 2 48 52 40 40
Fax : +33 2 48 71 04 97
Web site : www.honeywellsafety.com