

BU–1481–E–00–*
"Mini–Micro–Plunger" To 0.025" (0.6 mm) Square Pin

- No. 208 gold–plated one–piece beryllium copper conductor.
- Nylon stem and cap and stainless steel compression string.
- Attaches to 0.025" (.6mm) dia. and smaller component leads.
- Square Pin has gold–plated alloy 360 copper insert with ABS housing.
- #22 AWG wire (19/34) tinned copper with 105°C PVC insulation.
- **Product Data Sheet**
- Send us your questions about this product

BU–2020–A–00–*
Stackable Single Banana Plug— Both Ends

- Nine–leaf beryllium copper, nickel–plated spring.
- Double stacking ability.
- #20 AWG wire (41/36) tinned copper with 105°C PVC insulation.
- **Product Data Sheet & Compatibility Info**
- Send us your questions about this product


Enlarge


Click for Larger Image

BU–2030–A–00–*
Insulated Alligator Clip To Stackable Banana Plug

- Nickel–plated steel with PVC insulator; jaw opens to 5/16" (7.9 mm).
- Nine–leaf beryllium copper, nickel–plated spring.
- Double stacking ability.
- ‡20 AWG (41/36) tinned copper wire with 105°C PVC insulation.
- **Product Data Sheet & Compatibility Info**
- Send us your questions about this product



BU–2031–A–00–*
Insulated Mini–Alligator Clip To Stackable Banana Plug

- Nickel–plated steel with durable PVC insulator.
- Jaw opens to 3/16" (4.7 mm).
- Nine–leaf beryllium copper, nickel–plated spring.
- #20 AWG wire (41/36) tinned copper with 105°C PVC insulation.
- **Product Data Sheet & Compatibility Info**
- Send us your questions about this product

©1999-2000 Mueller Electric Company. All rights reserved.
Problems with the site should be reported to the webmaster.