TECHNICAL SPECIFICATION

Stealth™ 9000

Smoke PremierShield™ K & N Rated / ASA770-15W-900



DESCRIPTION

The Stealth™ 9000 is a lightweight safety spectacle, weighing just 25g, with a wraparound 9 base curve polycarbonate lens. The slim stylish temples have been co-injection moulded with soft rubber to increase grip and provide excellent comfort. Stealth™ 9000 is available in a range of lens shades for various applications, with the option to add branding with logos and company colours.

OPTIONS

Amber PremierShield™ K & N Rated (ASA770-15P-900)
Clear PremierShield™ K & N Rated (ASA770-15N-800)
GW5 Hardia+™ Anti-Scratch Lens (ASA770-1CN-800)
Indoor Outdoor Hardia™ HC lens. (ASA770-16R-100)
Polarised Smoke Hardia+™ HC lens (ASA770-16X-600)
Smoke + Blue Mirror Hardia™ HC lens (ASA770-16P-000)
Smoke PremierShield™ K & N Rated (ASA770-15W-900)

SAFETY STANDARDS

EN 172 • EN 166

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

RADIATION PROTECTION BREAKDOWN filtering effect Scale Number
5

Manufacturer's Trademark
JSP Dagger

Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s ˚ Maximum protection for glasses
F

Resistance to Surface Damage by Fine Particles (optional)
K

LIGHT TRANSMISSION BREAKDOWN Lens Shade number
2.5

Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1

The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5˚C and +55˚C) Optional
T

Resistance to fogging (optional)
N

FEATURES



Quality Lens

A lightweight safety spectacle, weighing just 25g. Features a wraparound 9.75 base curve Optical Class 1 polycarbonate lens precision cut for zero distortion.



Comfort Nose Bridge

Built-in adjustable PVC nose piece for added comfort and stability. It rotates, as well as flexes, and adjusts to fit the shape of the nose.



Comfort Temples

The slim stylish temples have been co-injection moulded with soft rubber to increase grip and provide excellent comfort levels.

RANGE

STEALTH 9000

DOWNLOADS

Image Pack (ZIP)
doc-stealth-9000-spectacle-range.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.