DATASHEET - S811+V50V3S

Soft starter, 500 A, 200 - 690 V AC, Us= 24 V DC, with control unit and pump algorithm, for 690-V grids, Frame size V

Part no.	**S811+V50V3S**
	169001
EL Number (Norway)	**4137485**

General specifications

Product name	Eaton S811 Soft starter
Part no.	S811+V50V3S
EAN	4015081654956
Product Length/Depth	187.8 millimetre
Product height	420.8 millimetre
Product width	280.6 millimetre
Product weight	41.4 kilogram
Certifications	UL UL 508 UL File No.: E202571 GB14048 CSA CCC UL Category Control No.: NMFT CE CSA22.2-14-1995 C-Tick IEC/EN 60947-4-2
Product Tradename	S811
Product Type	Soft starter
Product Sub Type	None
Catalog Notes	Terminal blocks for the terminals are required for frame sizes T, U, and V -> Accessories Regulator supply: External supply voltage External solution required (reversing contactor)

Features & Functions

Fault memory	10 Faults
Fitted with:	Internal bypass contacts Display Internal bypass Motor overload protection
Functions	Underload monitoring Current limitation Suppression of closing transients Suppression of DC components for motors Single direction Overload monitoring Potential isolation between power and control sections Soft start function Min. ramp time 1 s - fast switching (semiconductor contactor)
Interfaces	Modbus RTU (built-in)

General information

Class	Adjustable
Connection to SmartWire-DT	No
Degree of protection	NEMA Other IP00
Frame size	V
Mains voltage - min	200 V
Mains voltage - max	690 V
Mounting position	As required
Overvoltage category	II
Pollution degree	3
Radio interference class	Class A (EN 55011)
Rated impulse withstand voltage (Uimp)	4000 V
Shock resistance	15 g, Mechanical
Startup class	CLASS 30 (6 x I# for 30 s) CLASS 20 (heavy starting duty 3 x I# for 45 s)

	CLASS 10 (star-delta replacement)
Suitable for	Branch circuits, not as BCPD, (UL/CSA)
Type	Soft starter for three-phase loads, with control unit and pump algorithm, for 690-V grids
Voltage type	DC
Climatic environmental conditions	
Altitude	Above 2000 m with 0.5 % derating per 100 m Max. 2000 m
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	50 °C
Ambient storage temperature - min	-50 °C
Ambient storage temperature - max	70 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-3 Damp heat, cyclic, to IEC 60068-2-30
Main conducting paths	
Overload cycle	AC-53a: 4.0 - 32: 99 - 3
Rated operational current (Ie) at AC-53	500 A
Rated operational voltage (Ue) - min	200 V
Rated operational voltage (Ue) - max	690 V
Short-circuit protection rating	NZMN3-S500, Type “1” coordination, Main conducting paths
Supply frequency	50/60 Hz, fLN, Main circuit
Voltage rating - max	690 V
Motor rating	
Assigned motor power at 200/208 V, 60 Hz, 3-phase	150 HP
Assigned motor power at 220/230 V, 60 Hz, 3-phase	200 HP
Assigned motor power at 460/480 V, 60 Hz, 3-phase	400 HP
Assigned motor power at 600 V, 60 Hz, 3-phase	500 HP
Assigned motor power at 690 V, 60 Hz, 3-phase	600 HP
Assigned motor power in-delta at 690 V, 60 Hz	850 HP
Rated operational power at 220/230 V, 50 Hz	160 kW
Rated operational power at 400 V, 50 Hz	250 kW
Rated operational power at 500 V, 50 Hz	315 kW
Rated operational power at 690 V, 50 Hz	500 kW
Terminal capacities	
Terminal capacity (flexible with ferrule)	6 x (120 - 240) mm^2, Main cables 4 x (70 - 240) mm^2, Main cables 2 x (1 - 2.5) mm^2, Control circuit cables 1 x (2.5 - 4) mm^2, Control circuit cables 2 x (120 - 240) mm^2, Main cables
Terminal capacity (solid)	4 x (70 - 240) mm^2, Main cables 6 x (120 - 240) mm^2, Main cables 2 x (120 - 240) mm^2, Main cables 2 x (1 - 2.5) mm^2, Control circuit cables 1 x (2.5 - 4) mm^2, Control circuit cables
Terminal capacity (solid/stranded AWG)	2 x (14 - 12), Control circuit cables 2 x (4 - 500 kcmil), Main cables 1 x (14 - 12), Control circuit cables 6 x (4 - 500 kcmil), Main cables 4 x (4 - 500 kcmil), Main cables
Terminal capacity (stranded)	2 x (120 - 240) mm^2, Main cables 2 x (1 - 2.5) mm^2, Control circuit cables 4 x (70 - 240) mm^2, Main cables 6 x (120 - 240) mm^2, Main cables 1 x (2.5 - 4) mm^2, Control circuit cables
Screwdriver size	0.6 x 3.5 mm, Terminal screws, Control circuit cables
Tightening torque	0.4 Nm, Screw terminals, Control circuit cables
Control circuit	
Current consumption	1400 mA, Control circuit, Regulator supply 100 mA, Control circuit, Digital inputs, External 24 V (no-load) 150 mA, Control circuit, Digital inputs, External 24 V 10 A/150 ms, Control circuit, Regulator supply at peak performance (close bypass) at 24 V DC
Drop-out time	100 ms, DC operated
Drop-out voltage	0 - 3 V, DC operated

Pick-up time	100 ms at DC
Pick-up voltage	21.6 - 26.4 V DC
Rated control supply voltage (Us) at AC, 50 Hz - min	0 V
Rated control supply voltage (Us) at AC, 50 Hz - max	0 V
Rated control supply voltage (Us) at AC, 60 Hz - min	0 V
Rated control supply voltage (Us) at AC, 60 Hz - max	0 V
Rated control supply voltage (Us) at DC - min	24 V
Rated control supply voltage (Us) at DC - max	24 V

Input/Output

Input current	4 - 20 mA (Analog inputs)
Number of inputs	1 (current input)
Number of outputs	2 Relay Outputs (programmable)
Output voltage	120 V AC/DC (relay outputs)
Protection	Finger and back-of-hand proof, Protection against direct contact
Rated control voltage (Uc)	24 V DC (-10 %/+10 %) 24 V DC
Rated operational current (Ie) at AC-11	3 A

Soft start function

Application	Soft starting of three-phase asynchronous motors 3-phase motors: Yes
Delay time	0 - 120 s, Soft start function, Ramp times
Kickstart	100% (Kickstart voltage) Max. 2000 ms (Kickstart Duration)
Ramp/run-up time	360 s
Start voltage	Max. 85 %, Soft start function, Start voltage = turn-off voltage

Design verification

Equipment heat dissipation, current-dependent Pvid	25 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	500 A
Static heat dissipation, non-current-dependent Pvs	25 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Soft starter (EC000640)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Load breakout, motor breakout / Semiconductor motor controller or soft starter (ecl@ss13-27-37-09-07 [ACO300016])			
Rated operation current Ie at 40 °C Tu		A	500
Rated operating voltage Ue		V	200 - 690
Rated power three-phase motor, inline, at 230 V		kW	160
Rated power three-phase motor, inline, at 400 V		kW	250
Rated power three-phase motor, inside delta, at 230 V		kW	200
Rated power three-phase motor, inside delta, at 400 V		kW	450
Function			Single direction
Internal bypass			Yes
With display			Yes
Torque control			No
Rated surrounding temperature without derating		°C	50
Rated control supply voltage AC 50 Hz		V	0 - 0
Rated control supply voltage AC 60 Hz		V	0 - 0
Rated control supply voltage DC		V	24 - 24
Voltage type for actuating			DC
Integrated motor overload protection			Yes
Release class			Adjustable
Degree of protection (IP)			IP00
Degree of protection (NEMA)			Other

© 04/2023 by Eaton Industries GmbH