DATASHEET - EU1S-SWD-PF1-2



SWD power supply IP67 for 24VDC feeding 4 A in the SWD network

Part no. **EU1S-SWD-PF1-2**
174724

General specifications	
Product name	Eaton EU1S Accessory Power supply
Part no.	EU1S-SWD-PF1-2
EAN	4015081712106
Product Length/Depth	85.6 millimetre
Product height	20.1 millimetre
Product width	56.9 millimetre
Product weight	0.06 kilogram
Certifications	CSA File No.: 2324643 UL File No.: E29184 UL UL Category Control No.: NKCR IEC/EN 60529 IEC/EN 61131-2 EN 50178 CSA Class No.: 3211-07 CSA
Product Tradename	EU1S
Product Type	Accessory
Product Sub Type	Power supply
Features & Functions	
Electric connection type	Plug-in connection
Features	Fieldbus connection over separate bus coupler possible
Fitted with:	Potential separation Power supply module
Functions	For feeding supply voltage in order to connect additional SmartWire-DT modules (IP 67) and connected sensors/actuators
General information	
Degree of protection	IP67
Overvoltage category	II
Pollution degree	3
Product category	SmartWire-DT accessories
Residual ripple	≤ 5 % (input voltage)
Suitable as	Segment module
Voltage type	DC
Ambient conditions, mechanical	
Constant acceleration	1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations
Constant amplitude	3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations
Drop and topple	50 mm Drop height, Drop to IEC/EN 60068-2-31
Height of fall (IEC/EN 60068-2-32) - max	0.3 m
Mounting position	As required
Shock resistance	15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts
Climatic environmental conditions	
Air pressure	795 - 1080 hPa (operation)
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Ambient storage temperature - min	-40 °C
Ambient storage temperature - max	70 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-3 Dry heat to IEC 60068-2-2
Environmental conditions	Condensation: permissible
Operating temperature - min	-25 °C

Operating temperature - max	70 °C
Electro magnetic compatibility	
Air discharge	8 kV, according to IEC 61131-2, level 3, ESD
Burst impulse	2 kV, Supply cable, according to IEC/EN 61131-2, Level 3 1 kV, CAN/DP bus cable, Signal cable, according to IEC/EN 61131-2, Level 3 1 kV, SmartWire-DT cable, according to IEC/EN 61131-2, Level 3
Contact discharge	4 kV, according to IEC/EN 61131-2, Level 2, ESD
Electromagnetic fields	1 V/m at 2.0 - 2.7 GHz (according to IEC/EN 61131-2:2008) 3 V/m at 1.4 - 2 GHz (according to IEC/EN 61131-2:2008) 10 V/m at 80 - 1000 MHz (according to IEC/EN 61131-2:2008)
Radiated RFI	10 V (IEC/EN 61131-2:2008, Level 3)
Radio interference class	Class A (EN 55011)
Surge rating	0.5 kV, Supply cables/CAN/DP bus cable, Surge power cables, Surge (IEC/EN 61131-2:2008, Level 1), EMC
Electrical rating	
Power loss	Normally 1 W
Rated control supply voltage	24 V DC (UAUX, -15 %/+20 %)
Rated operational voltage	Typically UAUX -0.2 V (for 24 V DC slaves)
Short-circuit protection	No, external fuse FAZ Z3, Supply voltage UAux
Supply current	4 A, Imax, Supply voltage UAux
Supply voltage at AC, 50 Hz - min	0 V AC
Supply voltage at AC, 50 Hz - max	0 V AC
Supply voltage at DC - min	20.4 V DC
Supply voltage at DC - max	28.8 V DC
Communication	
Connection	SmartWire-DT plug connector SWD4-SM5-67 SmartWire-DT plug connector SWD4-SF5-67
Connection to SmartWire-DT	Yes
Connection type	5-pin M12 socket (A-keyed), Supply voltage SWD: Socket, plug M12 (A-keyed), 5 pole
Protocol	Other bus systems
Safety	
Explosion safety category for dust	None
Explosion safety category for gas	None
Potential isolation	Supply voltage UAUX: no
Protection against polarity reversal	Yes
Design verification	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	1 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Meets the product standard's requirements.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Programmable logic controllers PLC (EG000024) / Fieldbus, decentr. periphery - power supply/segment module (EC001600)

Electric engineering, automation, process control engineering / Control, Process Control System (PCS) / Field bus, decentralized peripheral / Field bus, decentralized peripheral - feed and segment module (ecl@ss13-27-24-26-10 [BAA071018])

Supply voltage AC 50 Hz		V	0 - 0
Supply voltage AC 60 Hz		V	0 - 0
Supply voltage DC		V	20.4 - 28.8
Voltage type (supply voltage)			DC
Number of HW-interfaces industrial Ethernet			0
Number of interfaces PROFINET			0
Number of HW-interfaces RS-232			0
Number of HW-interfaces RS-422			0
Number of HW-interfaces RS-485			0
Number of HW-interfaces serial TTY			0
Number of HW-interfaces parallel			0
Number of HW-interfaces wireless			0
Number of HW-interfaces USB			0
Number of HW-interfaces other			1
With optical interface			No
Supporting protocol for EtherCAT			No
Supporting protocol for TCP/IP			No
Supporting protocol for PROFIBUS			No
Supporting protocol for CAN			No
Supporting protocol for INTERBUS			No
Supporting protocol for ASI			No
Supporting protocol for KNX			No
Supporting protocol for Modbus			No
Supporting protocol for Data-Highway			No
Supporting protocol for DeviceNet			No
Supporting protocol for SUCONET			No
Supporting protocol for LON			No
Supporting protocol for PROFINET IO			No
Supporting protocol for PROFINET CBA			No
Supporting protocol for SERCOS			No
Supporting protocol for Foundation Fieldbus			No
Supporting protocol for EtherNet/IP			No
Supporting protocol for AS-Interface Safety at Work			No
Supporting protocol for DeviceNet Safety			No
Supporting protocol for INTERBUS-Safety			No
Supporting protocol for PROFIsafe			No
Supporting protocol for SafetyBUS p			No
Supporting protocol for other bus systems			Yes
Radio standard Bluetooth			No
Radio standard WLAN 802.11			No
Radio standard GPRS			No
Radio standard GSM			No
Radio standard UMTS			No

System accessory			Yes
Degree of protection (IP)			IP67
Type of electric connection			Plug-in connection
With potential separation			Yes
With power supply module			Yes
Suitable as segment module			Yes
Remote module			No
Fieldbus connection over separate bus coupler possible			Yes
Bus diagnosis possible			No
Rail mounting possible			Yes
Wall mounting/direct mounting			Yes
Front built-in possible			No
Rack-assembly possible			No
Suitable for safety functions			No
SIL according to IEC 61508			None
Performance level according to EN ISO 13849-1			None
Appendant operation agent (Ex ia)			No
Appendant operation agent (Ex ib)			No
Explosion safety category for gas			None
Explosion safety category for dust			None
Certified for UL hazardous location class I			No
Certified for UL hazardous location class II			No
Certified for UL hazardous location class III			No
Certified for UL hazardous location division 1			No
Certified for UL hazardous location division 2			No
Certified for UL hazardous location group A (acetylene)			No
Certified for UL hazardous location group B (hydrogen)			No
Certified for UL hazardous location group C (ethylene)			No
Certified for UL hazardous location group D (propane)			No
Certified for UL hazardous location group E (metal dusts)			No
Certified for UL hazardous location group F (carbonaceous dusts)			No
Certified for UL hazardous location group G (non-conductive dusts)			No
Width		mm	56.9
Height		mm	20.1
Depth		mm	85.6

© 04/2023 by Eaton Industries GmbH