PREVO S1 Quick release safety couplings one push - ISI 06


ISI 062101

Bulkhead coupler



Technical characteristics

- **Technology:** "One push" safety system (avoids hose whip)
- **Operating pressure:** 2 to 12 bar
- **Flow rate at 6 bar:** 833 l/min (ΔP = 0,6 bar)
- **ID Passage:** 6 mm
- **Temperature:** -15°C to +70°C
- **Construction:** Composite body
- **Highlight:** Anti-static, Non scratch



A (mm)	B (mm)	C (mm)	D (mm)	BSPP female thread	Drill Ø (mm)	Panel thickness (mm)	Parts Numbers
84	30	29	32	G 1/4	27	11	**ISI 062101**

PREVOST UK - G, Tower Business Park, Commercial Rd, Darwen BB3 0FJ - United Kingdom
Tel. : (+44) 0844 800 2788 - Fax : (+44) 0844 800 2789 - E-mail : sales@prevost-ltd.co.uk - www.prevost.eu International = PREVOST SAS - - C.S. 90208 - 74942 ANNECY-LE-VIEUX CEDEX - France Tel. : +33 (4)50 64 04 45 - Fax : +33 (0)4 50 64 00 10 - E-mail : sales@prevost.eu- www.prevost.eu

This document is non-contractual. PREVOST reserves the right to modify the features of its range without prior notice.