# DATASHEET - M22S-DP-Y-X

**Mushroom actuator, RMQ-Titan, Mushroom, momentary, Mushroom yellow, Without button plate, Bezel: black**

**Part no.** **M22S-DP-Y-X**
**216739**

| | |
|---|---|
| Product name | Eaton Moeller® series M22 Mushroom actuator |
| Part no. | M22S-DP-Y-X |
| EAN | 4015082167394 |
| Product Length/Depth | 37 millimetre |
| Product height | 43 millimetre |
| Product width | 37 millimetre |
| Product weight | 0.016 kilogram |
| Certifications | CSA-C22.2 No. 94-91<br>IEC/EN 60947-5<br>UL<br>CE<br>CSA<br>CSA File No.: 012528<br>UL Category Control No.: NKCR<br>VDE 0660<br>UL 508<br>CSA-C22.2 No. 14-05<br>UL File No.: E29184<br>CSA Class No.: 3211-03<br>IEC/EN 60947<br>DNV<br>LR<br>GL |
| Product Tradename | M22 |
| Product Type | Mushroom actuator |
| Product Sub Type | None |
| | |
| Bezel color | Black |
| Bezel material | Plastic |
| Design | Mushroom-shaped<br>Classical |
| Fitted with: | Front ring |
| Unlocking method | None |
| | |
| Degree of protection | IP67/IP69K<br>NEMA 4X, 13 |
| Lifespan, mechanical | 5,000,000 Operations |
| Opening diameter | 22.5 mm |
| Operating frequency | 3600 Operations/h |
| Product category | RMQ-Titan |
| Size | Front dimensions: 22 x 22 mm |
| Type | Mushroom-headed pushbutton |
| | |
| Mounting position | As required |
| Shock resistance | 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms<br>Mechanical, According to IEC/EN 60068-2-27 |
| | |
| Ambient operating temperature - min | -25 °C |
| Ambient operating temperature - max | 70 °C |
| Ambient storage temperature - min | 40 °C |
| Ambient storage temperature - max | 80 °C |
| Climatic proofing | Damp heat, cyclic, to IEC 60068-2-30<br>Damp heat, constant, to IEC 60068-2-78 |
| | |
| Connection to SmartWire-DT | Yes |

| | | | |
|---|---|---|---|
| | | | With SWD-RMQ connections |
| | | | |
| Actuating force | | | 5 N |
| Actuator color | | | Yellow |
| Actuator function | | | Momentary<br>Spring-return |
| | | | |
| Force for positive opening - min | | | 0 N |
| | | | |
| Equipment heat dissipation, current-dependent Pvid | | | 0 W |
| Heat dissipation capacity Pdiss | | | 0 W |
| Heat dissipation per pole, current-dependent Pvid | | | 0 W |
| Rated operational current for specified heat dissipation (In) | | | 0 A |
| Static heat dissipation, non-current-dependent Pvs | | | 0 W |
| 10.2.2 Corrosion resistance | | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | Please enquire |
| 10.2.5 Lifting | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | | Not applicable. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Front element for mushroom push-button (EC001038)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for mushroom push-button actuators (ecl@ss10.0.1-27-37-12-12 [AKF030014])

| | | | |
|---|---|---|---|
| Colour button | | | Yellow |
| Construction type lens | | | Round |
| Diameter cap | | mm | 36.5 |
| Hole diameter | | mm | 22.5 |
| Width opening | | mm | 0 |
| Height opening | | mm | 0 |
| Degree of protection (IP) | | | IP67/IP69K |
| Degree of protection (NEMA) | | | 4X, 13 |
| Type of button | | | Flat |
| Suitable for illumination | | | No |
| With lighting | | | No |
| Supply voltage lamp | | V | 0 |
| Switching function latching | | | No |
| Spring-return | | | Yes |

| | | | |
|---|---|---|---|
| With front ring | | | Yes |
| Material front ring | | | Plastic |
| Colour front ring | | | Black |
| Suitable for emergency stop | | | No |
| Unlocking method | | | None |


© 04/2023 by Eaton Industries GmbH