DATASHEET - EVG-16/3PHAS/12MODUL



EV busbars 3Ph., 12HP, 80A for PLS. CLS. PKN., PFIM, PFHM, PFNM

Part no.	**EVG-16/3PHAS/12MODUL**
Catalog No.	**291472**
EL-Nummer (Norway)	**1605381**

Similar to illustration

Delivery program

Basic function			Busbar
Basic function accessories			Busbar for miniature circuit-breaker Busbar for residual-current circuit-breakers Busbar for combined residual-current/power circuit-breaker
Busbar type			Three-phase
Product range			EVG

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss8.1-27-37-13-06 [ACN992008])

Number of phases			3
Number of poles			3
Suitable for number of devices			4
Pitch dimensions		mm	0
Cross section		mm^2	16
Length		mm	213.6
Number of modular spacings			12
Rated permanent current Iu		A	80
Type of electric connection			Fork
Insulated			Yes
Rated surge voltage		kV	4
Conditioned rated short-circuit current Iq		kA	25
Max. rated operation voltage Ue		V	415
Rated short-time withstand current Icw		kA	0
Suitable for devices with N-busbar			No
Suitable for devices with auxiliary switch			No

Dimensions



Eaton Industries GmbH
http://www.eaton.eu
© 07/2022 by Eaton Industries GmbH