Datasheet

RS PRO 0.5” COATING BRUSH

Stock No: **2009209,2009210,2009211,2009212, 2009213,2009215,2009216**

ENGLISH



KEY FEATURES

Unique blend of synthetic bristle

Solid, chemical resistant plastic handle

Ergonomic American shaped handle

0.5”/12mm brush size

Stainless Steel Ferrule

DESCRIPTION | 0.5” Laminating Brush

HEAD SIZE | 0.5” / 12mm

TRIM LENGTH | 45mm

FILL MATERIAL | Synthetic Bristle

HANDLE | Chemical Resistant Plastic

SURFACE PRIMING | UNDERCOATING | TOP COATING

Ideal for use with all coating types. The unique blend of synthetic bristle has been formulated to have a high pick-up rating whilst being able to work the medium out in an even application. Our American shaped handle makes this brush perfect for flat filling large areas or used on its edge for detail work.

TESTED AND APPROVED FOR USE WITH THE FOLLOWING COATINGS:

AKZO NOBEL INTERFINE INTERNATIONAL

International Interfine is part of International’s premium range of polysiloxane finishes. It is designed to provide excellent long-term colour and gloss retention and provide extended lifetime to first maintenance when utilised as part of a high performance anti-corrosive system.

AKZO NOBEL INTERZINC 22 INTERSEAL

International Interzinc 22 is a two component, rapid recoat, inorganic zinc rich ethyl silicate primer and is part of the Interzinc 22 Series of products that deliver consistently fast re-coating across a choice of 85%, 80%, 77% or 65% minimum zinc content products. The variable zinc levels allow you to tailor your choice of product to meet NORSOK, SSPC Paint 20 or ISO 12944 standards.

COO-VAR® LOW ODOUR LINE MARKING PAINT

Low odour line marking paint is a spirit based paint which can be applied directly to tarmac, sealed concrete and wood. It is ideal for use in factories and schools where fast drying is a high priority.

Datasheet

RS PRO 1” COATING BRUSH

Stock No: **2009209,2009210,2009211,2009212, 2009213,2009215,2009216**

ENGLISH



KEY FEATURES

Unique blend of synthetic bristle

Solid, chemical resistant plastic handle

Ergonomic American shaped handle

1”/25mm brush size

Stainless Steel Ferrule

DESCRIPTION | 1” Laminating Brush

HEAD SIZE | 1” / 25mm

TRIM LENGTH | 50mm

FILL MATERIAL | Synthetic Bristle

HANDLE | Chemical Resistant Plastic

SURFACE PRIMING | UNDERCOATING | TOP COATING

Ideal for use with all coating types. The unique blend of synthetic bristle has been formulated to have a high pick-up rating whilst being able to work the medium out in an even application. Our American shaped handle makes this brush perfect for flat filling large areas or used on its edge for detail work.

TESTED AND APPROVED FOR USE WITH THE FOLLOWING COATINGS:

AKZO NOBEL INTERFINE INTERNATIONAL

International Interfine is part of International’s premium range of polysiloxane finishes. It is designed to provide excellent long-term colour and gloss retention and provide extended lifetime to first maintenance when utilised as part of a high performance anti-corrosive system.

AKZO NOBEL INTERZINC 22 INTERSEAL

International Interzinc 22 is a two component, rapid recoat, inorganic zinc rich ethyl silicate primer and is part of the Interzinc 22 Series of products that deliver consistently fast re-coating across a choice of 85%, 80%, 77% or 65% minimum zinc content products. The variable zinc levels allow you to tailor your choice of product to meet NORSOK, SSPC Paint 20 or ISO 12944 standards.

COO-VAR® LOW ODOUR LINE MARKING PAINT

Low odour line marking paint is a spirit based paint which can be applied directly to tarmac, sealed concrete and wood. It is ideal for use in factories and schools where fast drying is a high priority.

Datasheet

RS PRO 1.5” COATING BRUSH

Stock No: **2009209,2009210,2009211,2009212, 2009213,2009215,2009216**

ENGLISH



KEY FEATURES

Unique blend of synthetic bristle

Solid, chemical resistant plastic handle

Ergonomic American shaped handle

1.5”/38mm brush size

Stainless Steel Ferrule

DESCRIPTION | 1.5” Laminating Brush

HEAD SIZE | 1.5” / 38mm

TRIM LENGTH | 55mm

FILL MATERIAL | Synthetic Bristle

HANDLE | Chemical Resistant Plastic

SURFACE PRIMING | UNDERCOATING | TOP COATING

Ideal for use with all coating types. The unique blend of synthetic bristle has been formulated to have a high pick-up rating whilst being able to work the medium out in an even application. Our American shaped handle makes this brush perfect for flat filling large areas or used on its edge for detail work.

TESTED AND APPROVED FOR USE WITH THE FOLLOWING COATINGS:

AKZO NOBEL INTERFINE INTERNATIONAL

International Interfine is part of International’s premium range of polysiloxane finishes. It is designed to provide excellent long-term colour and gloss retention and provide extended lifetime to first maintenance when utilised as part of a high performance anti-corrosive system.

AKZO NOBEL INTERZINC 22 INTERSEAL

International Interzinc 22 is a two component, rapid recoat, inorganic zinc rich ethyl silicate primer and is part of the Interzinc 22 Series of products that deliver consistently fast re-coating across a choice of 85%, 80%, 77% or 65% minimum zinc content products. The variable zinc levels allow you to tailor your choice of product to meet NORSOK, SSPC Paint 20 or ISO 12944 standards.

COO-VAR® LOW ODOUR LINE MARKING PAINT

Low odour line marking paint is a spirit based paint which can be applied directly to tarmac, sealed concrete and wood. It is ideal for use in factories and schools where fast drying is a high priority.

Datasheet

RS PRO 2” COATING BRUSH

Stock No: **2009209,2009210,2009211,2009212, 2009213,2009215,2009216**

ENGLISH



KEY FEATURES

Unique blend of synthetic bristle

Solid, chemical resistant plastic handle

Ergonomic American shaped handle

2”/50mm brush size

Stainless Steel Ferrule

DESCRIPTION | 2” Laminating Brush

HEAD SIZE | 2” / 50mm

TRIM LENGTH | 60mm

FILL MATERIAL | Synthetic Bristle

HANDLE | Chemical Resistant Plastic

SURFACE PRIMING | UNDERCOATING | TOP COATING

Ideal for use with all coating types. The unique blend of synthetic bristle has been formulated to have a high pick-up rating whilst being able to work the medium out in an even application. Our American shaped handle makes this brush perfect for flat filling large areas or used on its edge for detail work.

TESTED AND APPROVED FOR USE WITH THE FOLLOWING COATINGS:

AKZO NOBEL INTERFINE INTERNATIONAL

International Interfine is part of International’s premium range of polysiloxane finishes. It is designed to provide excellent long-term colour and gloss retention and provide extended lifetime to first maintenance when utilised as part of a high performance anti-corrosive system.

AKZO NOBEL INTERZINC 22 INTERSEAL

International Interzinc 22 is a two component, rapid recoat, inorganic zinc rich ethyl silicate primer and is part of the Interzinc 22 Series of products that deliver consistently fast re-coating across a choice of 85%, 80%, 77% or 65% minimum zinc content products. The variable zinc levels allow you to tailor your choice of product to meet NORSOK, SSPC Paint 20 or ISO 12944 standards.

COO-VAR® LOW ODOUR LINE MARKING PAINT

Low odour line marking paint is a spirit based paint which can be applied directly to tarmac, sealed concrete and wood. It is ideal for use in factories and schools where fast drying is a high priority.

Datasheet

RS PRO 3” COATING BRUSH

Stock No: **2009209,2009210,2009211,2009212, 2009213,2009215,2009216**

ENGLISH



KEY FEATURES

Unique blend of synthetic bristle

Solid, chemical resistant plastic handle

Ergonomic American shaped handle

3”/75mm brush size

Stainless Steel Ferrule

DESCRIPTION | 3” Laminating Brush

HEAD SIZE | 3” / 75mm

TRIM LENGTH | 70mm

FILL MATERIAL | Synthetic Bristle

HANDLE | Chemical Resistant Plastic

SURFACE PRIMING | UNDERCOATING | TOP COATING

Ideal for use with all coating types. The unique blend of synthetic bristle has been formulated to have a high pick-up rating whilst being able to work the medium out in an even application. Our American shaped handle makes this brush perfect for flat filling large areas or used on its edge for detail work.

TESTED AND APPROVED FOR USE WITH THE FOLLOWING COATINGS:

AKZO NOBEL INTERFINE INTERNATIONAL

International Interfine is part of International’s premium range of polysiloxane finishes. It is designed to provide excellent long-term colour and gloss retention and provide extended lifetime to first maintenance when utilised as part of a high performance anti-corrosive system.

AKZO NOBEL INTERZINC 22 INTERSEAL

International Interzinc 22 is a two component, rapid recoat, inorganic zinc rich ethyl silicate primer and is part of the Interzinc 22 Series of products that deliver consistently fast re-coating across a choice of 85%, 80%, 77% or 65% minimum zinc content products. The variable zinc levels allow you to tailor your choice of product to meet NORSOK, SSPC Paint 20 or ISO 12944 standards.

COO-VAR® LOW ODOUR LINE MARKING PAINT

Low odour line marking paint is a spirit based paint which can be applied directly to tarmac, sealed concrete and wood. It is ideal for use in factories and schools where fast drying is a high priority.