DATASHEET - SOL30X4-SAFETY-MV-U(230V50HZ)

Fireman's switch, for 4 strings, 25A, MV

Part no.	**SOL30X4-SAFETY-MV-U(230V50HZ)**
	168103
EL Number (Norway)	**4300335**

General specifications	
Product name	Eaton Moeller® series SOL30 Safety Fireman's switch
Part no.	SOL30X4-SAFETY-MV-U(230V50HZ)
EAN	4015081646807
Product Length/Depth	150 millimetre
Product height	405 millimetre
Product width	375 millimetre
Product weight	6.8 kilogram
Certifications	IEC/EN 60 947-3
Product Tradename	SOL30 Safety
Product Type	Fireman's switch
Product Sub Type	None
Features & Functions	
Actuator type	Turn button
Enclosure material	Plastic
Features	Complete device in housing
Fitted with:	Retraction in 0-position 0 (off) position
Number of poles	Two-pole
General information	
Application	Utility buildings Residential buildings
Connection type	M12, Outputs M12, Inputs
Degree of protection	IP65
Degree of protection (front side)	NEMA Other IP65
Lifespan, electrical	1,500 Operations
Lifespan, mechanical	100,000 Operations
Model	On/Off switch
Operating frequency	120 Operations/h
Overvoltage category	III
Pollution degree	3
Product Category	Switchgear for photovoltaic systems Fireman's Switch
Rated impulse withstand voltage (Uimp)	8000 V
Suitable for	Ground mounting
Utilization category	DC-PV2 (EN 60947-3) DC-PV1 (EN 60947-3) DC-21 A
Climatic environmental conditions	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	60 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Contacts	
Number of auxiliary contacts (change-over contacts)	0
Number of auxiliary contacts (normally closed contacts)	1
Number of auxiliary contacts (normally open contacts)	1
Electrical rating	
Rated operational current (Ie)	10 A at DC-PV2

			26 A at DC-PV1
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V			0 A
Rated operational power at AC-3, 380/400 V, 50 Hz			0 kW
Rated operational voltage (Ue) at AC - max			1000 V
Rated uninterrupted current (Iu)			30 A
Resistance			7 mΩ (internal)
Short-circuit rating			
Rated short-circuit making capacity (Icm)			0.32 kA (up to 440 V, 50/60 Hz)
Rated short-time withstand current (Icw)			0.36 kA

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Off-load switch (EC001105)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Load-break switch (ecl@ss13-27-37-14-05 [AKF062018])

Model			On/Off switch
Number of poles			2
With zero (off) position			Yes
With retraction in 0-position			Yes
Rated permanent current Iu		A	30
Rated operation current Ie at AC-3, 400 V		A	0
Rated operation power at AC-3, 400 V		kW	0
Degree of protection (IP), front side			IP65
Degree of protection (NEMA), front side			Other
Number of auxiliary contacts as normally closed contact			1
Number of auxiliary contacts as normally open contact			1
Number of auxiliary contacts as change-over contact			0
Suitable for floor mounting			Yes
Suitable for front mounting			No
Suitable for distribution board installation			No
Suitable for intermediate mounting			No
Complete device in housing			Yes
Housing material			Plastic
Type of control element			Turn button
Type of electrical connection of main circuit			Screw connection

© 04/2023 by Eaton Industries GmbH