# DATASHEET - 80A 415V AC HOUSE SERVICE




**Fuse-link, low voltage, 80 A, AC 415 V, 33 kA, BS system C type II, 23 x 57 mm, gL/gG, BS**

Powering Business Worldwide

**Part no.** 80A 415V AC HOUSE SERVICE
**Catalog No.** 80KR85

## Delivery program

| | | | |
|---|---|---|---|
| Product range | | | Fuse |
| Basic function | | | House service fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 80 |
| Rated voltage | | | AC 415 V |
| Construction size | | | BS system C type II |
| Size | | | 23 x 57 mm |
| Utilization category | | | gL/gG |
| Breaking Capacity | | kA | 33 |
| usable for size/applications | | | protection of incoming cables into residential and commercial properties |
| Standard/Approval | | | BS |
| Shape | | | cylindrical |
| Standards/Regulations | | | BS88-3 |

## Technical data ETIM 7.0

| | | | |
|---|---|---|---|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013]) | | | |
| Size | | | Other |
| Rated voltage | | V | 415 - 415 |
| Rated voltage | | | Other |
| Voltage type | | | AC |
| Utilization category | | | gL/gG (cable protection/equipment protection) |
| Rated operating frequency | | Hz | 45 - 62 |
| Nominal current | | A | 80 |
| With striker | | | No |
| Release characteristic | | | Other |
| Breaking capacity | | kA | 33 |


Eaton Industries GmbH
http://www.eaton.eu
© 02/2021 by Eaton Industries GmbH