Date: 12/04/2023

PCA2GA 3 … 25 bar Adaptor G 1/2 A-M , 1/2 -14 NPT-F

Compact pressure switch, flameproof Enclosure Ex d

Item number: 48782326

Quantity: 1 pcs.

Order code: PCA2GA-BAOC-4ASZZZ1ZZ CZKW
B000500DZZZZZZZZ
F4-C5- - - - -

Overview:
PCA2GA 3 … 25 bar Adaptor G 1/2 A-M , 1/2 -14 NPT-F
Compact pressure switch, flameproof Enclosure Ex d PCA
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Diaphragm Hastelloy C276
Connection: Stainless steel AISI 316L
contact version: 1xSPDT, silver contact
3 … 25 bar, working range 0 … 250 bar, proof pressure 400 bar
Process connection: Adaptor G 1/2 A-M
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case
Ingress Protection: IP66
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 33.31
Repeatability of set point: ≤ 1% of end of setting range

1. set point: 5.00 bar decreasing,

Approvals / Certificates
IECEx-ATEX Ex d

Details:
Compact pressure switch, flameproof Enclosure Ex d
Model PCA
Specifications according to data sheet: PV 33.31
Repeatability of set point: ≤ 1% of end of setting range
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Diaphragm Hastelloy C276
1xSPDT, silver contact
3 … 25 bar, working range 0 … 250 bar, proof pressure 400 bar
Process connection: Adaptor G 1/2 A-M
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case
Approvals / Certificates: with
Brand: WIKA Instruments Italia
Ingress Protection: IP66
PCA2GA 3 … 25 bar
1. set point: 5.00 bar decreasing,

© 2023 - WIKA Instruments s.a.r.l.

Date: 12/04/2023

Approvals / Certificates
IECEx-ATEX Ex d

© 2023 - WIKA Instruments s.a.r.l.