

DIRIS B

Multifunction measuring unit - PMD

measurement, monitoring and event analysis with smart sensors - modular format

Single-circuit metering, measurement & analysis



diris-b_038.eps

DIRIS B-10 / B-30
RS485

Configuration with Easy Config System.

The solution for

- Industry
- Building
- Infrastructure
- Local authority



Strong points

- Plug & Play
- Global accuracy class 0.5 in accordance with IEC 61557-12
- Multi-circuit
- Communication

Integrated technologies

PreciSense AutoCorrect VirtualMonitor

For more information see our website www.socomec.com

Conformity to standards

- UL E257746
- IEC 61557-12
- EN 50160
- ISO 14025

Function

The **DIRIS B** is a power monitoring device in a modular format that communicates via RS485. The 4 RJ12 independent current inputs of the device allow it to manage several types and number of circuits: for example, 4 single-phase loads or 1 three-phase load + 1 single-phase load.

The DIRIS B is connected to current sensors (RJ12 connection) that are suitable for all types of installation: solid TE, split-core TR/iTR, and flexible TF current sensors.

Advantages

Plug & Play

A rapid RJ12 connection makes wiring easy and reliable and prevents wiring errors. Automatically addressing and configuring the product (communication address, load type, type and ratio of current sensor) allow you to simplify implementation and to save time.

Class 0.5 in accordance with IEC 61557-12

- Class 0.2 for the meter alone.
- Class 0.5 from 2% to 120% of nominal current for the global measurement chain (associated with TE/iTR/TF current sensors).

Multi-circuit

- 4 current measurement inputs allow you to configure multiple circuits in order to optimise the number of measurement devices per installation.

Communication


- The DIRIS B can be connected to:
  - a remote DIRIS D-30 screen for displaying measurement and metering data.
  - DIRIS Digiware M-50/M-70 gateways for centralisation and communication of data via Ethernet. DIRIS Digiware M-70 embeds WEBVIEW-M, a webserver for remote visualisation of measurement data.
  - optional modules for more communication options including a second RS485 port or PROFIBUS DP protocol. Digital or Analog input/output, as well as temperature input modules can also be connected.

Application	Local metering	Local analysis
		
DIRIS B	***B-10*** RS485	***B-30*** RS485
Number of current inputs		
	4	4
Metering		
± kWh, ± kvarh, kVAh	•	•
Load curves		•
Multi-tariff	•	•
Multi-measurement		
U12, U23, U31, V1, V2, V3, f	•	•
U system, V system	•	•
I1, I2, I3, In, ΣP, ΣQ, ΣS, ΣPF	•	•
P, Q, S, PF per phase	•	•
Predictive power	•	•
Ph/N unbalance	•	•
Ph/Ph unbalance	•	•
Current unbalance (Inba, Idir, Iinv, Ihom, Inb)	•	•
Phi, cos Phi, tan Phi	•	•
Quality analysis		
THDv1, THDv2, THDv3, THDu12, THDu23, THDu31	•	•
THDi1, THDi2, THDi3, THDin	•	•
Individual harmonics U & V (up to 63rd)		•
Individual harmonics I (up to 63rd)		•
Crest factor I1, I2, I3, In		•
Crest factor V1, V2, V3, U12, U23, U31		•
Voltage dips, interruptions, swells (EN 50160)		•
Overcurrents		•
Alarms		
On threshold		•
Inputs/outputs		•
History of average values		
45 days (max)		•
Communication		
RS485 Modbus	•	•
2 inputs (status/pulse)	•	•

Accessories

DIRIS B sealing cover

- Prevents access to the cabling of the monitoring device.



USB configuration cable (2 m)

- Advanced configuration of DIRIS B gateways can be achieved using the EASY CONFIG software via Ethernet or direct USB connection.

DIRIS B

Multifunction measuring unit - PMD

measurement, monitoring and event analysis with smart sensors - modular format


DIRIS D-30 display

DIRIS D-30



diris-d_001_a_1_cat

Connection



diris-d_004_b_1_x_cat


Optional modules

DIRIS O



diris-b_031_a

Optional module ***DIRIS B***



Optional modules (4 max.)*

- Digital inputs/outputs
- Analogue inputs/outputs
- Temperature inputs
- Communication protocols

** maximum 4 optional modules with maximum 1 temperature module and 1 communication module (Modbus, PROFIBUS).*



diris-o_019_a

DIRIS O-iod

- 2 digital inputs centralises the metering pulses or the input status changes of the auxiliary contacts.
- 2 digital outputs can be connected to configurable alarms warning of exceeded thresholds (power, current, etc.) or can be piloted remotely.



diris-o_018_a

DIRIS O-ioa

- 2 inputs (4-20 mA) centralise analogue sensors (pressure, humidity, temperature, etc.)
- 2 outputs (4-20 mA) report the measurements (power, currents, etc.) to PLCs.



diris-o_020_a

DIRIS O-it

- 3 temperature inputs to be connected to PT100 or PT1000 sensors.
- Ambient air temperature.



diris-o_024_a

DIRIS O-m

- Provides a second RS485 Modbus communication port to the DIRIS B for simultaneous sending of information via RS485 to two supervision stations.




diris-o_023_a

DIRIS O-p


- Adds a PROFIBUS DPV1 communication port to the DIRIS B.

socomec Innovative Power Solutions


DIRIS B terminals



Current measurement




Voltage measurement and auxiliary power supply




Self supply

Easy connection of the power supply from the measurement terminal (specific terminals)




1. Fuses 0.5 A gG / 0.5 A class CC.

Separate power supply




1. Fuses 0.5 A gG / 0.5 A class CC.


2 inputs supplied by the product



2 inputs with external power supply




RS485




RJ9 for DIRIS D-30

(self-supply and data)




Terminals of optional DIRIS O modules


Optional module power supply




DIRIS O-iod




DIRIS O-ioa




DIRIS O-it



DIRIS O-m RS485



DIRIS O-p




Connections

Associated current sensors


Various types of current sensors can be connected to the DIRIS B: solid-core TE , split-core TR/iTR, flexible TF current sensors. This range of sensors can be adapted to all types of new or existing installations. A rapid RJ12 connection makes wiring easy and reliable and prevents wiring errors. The DIRIS B automatically recognises the type of sensor used and its current rating. This guarantees the overall accuracy of the DIRIS B + current sensor measurement chain.
For more information: see “TE, TR/iTR, TF sensors” pages.


TE solid-core current sensors



TR/iTR split-core current sensors

TF flexible current sensors






Network and connection examples


Three-phase + neutral

3P+N - 4CTs (measurement for 1 three-phase load + Neutral)




Three-phase

3P - 2CTs (2 three-phase loads without neutral)




Three-phase

3P+N - 3CTs & 1P+N - 1CT (1 three-phase load & 1 single-phase load)



Single-phase

1P+N-1CT (4 single-phase loads)




1. Fuses 0.5 A gG / 0.5 A class CC.
In case of self-supply, a fuse must be added on the neutral.


CT: Current sensors 3~ Load

Dimensions (mm)

DIRIS B




DIRIS O optional modules




DIRIS O optional modules	A (mm)
DIRIS O-iod - DIRIS O-ioa - DIRIS O-it	45
DIRIS O-m - DIRIS O-p	54

DIRIS D-30



Communication architecture

Example of communication architecture with DIRIS Digiware M-70 gateway and WEBVIEW-M embedded web server.



DIRIS B characteristics

Electrical characteristics

Auxiliary power supply	
AC voltage	110-230 VAC ±15 % (Ph/N ou Ph/Ph) Cat III
Frequency	50/60 Hz
Consumption	< 2 VA without display < 6VA with display
Connection	Removable spring-cage terminal, 2 x 2 positions, 0.5 … 2.5 mm² solid cable or 0.25 … 1.5 mm² stranded cable with ferrule

Measurement characteristics

Energy and power measurement	
Accuracy Active energy and active power	Class 0.2 DIRIS B alone Class 0.5 with TE, iTR or TF current sensors Class 1 with TR current sensors
Reactive energy accuracy	Class 2 with TE, TR or TF current sensors
Power factor measurement	
Accuracy	Class 0.5 with TE, iTR or TF current sensors Class 1 with TR current sensors
Voltage measurement	
Network characteristics measured	50-300VAC (Ph/N) - 87-520VAC (Ph/Ph) - CAT III
Frequency range	45 … 65Hz
Frequency accuracy	Class 0.02
Network type	Single-phase / Two-phase / Two-phase with neutral / Three-phase / Three-phase with neutral
Measurement by voltage transformer	Primary: 400 000 VAC Secondary: 60, 100, 110, 173, 190 VAC
Input consumption	≤ 0.1 VA
Permanent overload	300VAC Ph/N
Voltage measurement accuracy	Class 0.2
Connection	Removable spring-cage terminal, 2 x 6 positions, 0.5 … 2.5 mm² solid cable or 0.25 … 1.5 mm² stranded cable with ferrule
Current measurement	
Number of current inputs	4
Associated current sensors	Solid TE , split-core TR/iTR , flexible TF current sensors
Accuracy	Class 0.2 DIRIS B alone Class 0.5 with TE, iTR or TF current sensors Class 1 with TR current sensors
Connection	RJ12 connectors with specific SOCOMEC cable

Input characteristics

Number	2
Type / Power supply	Optocoupler internal polarisation (12 VDC ± 10 %) or external polarisation (10-30 VDC ± 10%)
Input function	Logic status, pulse meter or synchronisation pulse status (input 1)

Communication characteristics

DIRIS B RS485	
Link	RS485
Connection type	2 … 3 half duplex wires
Protocol	Modbus RTU
Speed	1200 … 115200 bauds
USB	DIRIS B RS485 configuration

Environment characteristics

Operating temperature	-10 … +70 °C
Storage temperature	-25 … +85 °C
Operating humidity	55 °C / 97% relative humidity
Operating altitude	2000 m
Vibration	1G from 10 to 100Hz

DIRIS D-30 display characteristics

Mechanical characteristics	
Screen type	Capacitive touch-screen technology, 10 keys
Screen resolution	350 x 160 pixels
Single product connection	
RJ9	Self-supply and data
Micro-USB	Updating
Degree of protection	IP65 (front face)
Environment	
Storage temperature (°C)	-20 ... +70°C
Operating temperature (°C)	-20 ... +70°C
Humidity	95 % to 40°C
Installation category	CAT III
Degree of pollution	2

DIRIS O optional modules characteristics

Power supply(1)	
AC voltage	110-230 VAC ±15 %
Frequency	50/60 Hz

(1) No power supply on DIRIS O-it.

DIRIS O-iod - 2 digital inputs/2 digital outputs	
Number of inputs	2 per optional modules - max. 4 optional modules
Type	Optocoupler internal polarisation (12 VDC ± 10 %) or external polarisation (10-30 VDC ± 10%)
Function	Logic status or pulse meter
Number of outputs	2 per optional modules - max. 4 optional modules
Type	Relay / 230 VAC ±15 % - 1 A
Function	Configurable alarm (current, power…) on threshold overruns or remote controlled status
Inputs/Outputs connection	Removable screw terminal, 4 positions, 0.14 to 1.5 mm² stranded or solid cable
DIRIS O-ioa - 2 analogue inputs/2 analogue outputs	
Number of inputs	2 per optional modules - max. 4 optional modules
Type	4-20 mA
Function	Connection of analogue sensors (pressure, humidity, temperature…)
Number of outputs	2 per optional modules - max. 4 optional modules
Type	4-20 mA
Function	Transmission of measurement image (current, power…) to PLCs
DIRIS O-it - 3 temperature inputs	
Number of inputs	3 external inputs + 1 measurement for ambient temperature
Dynamic	-20 … 150 °C
Type	PT100 or PT1000
Function inputs 1, 2 and 3	Temperature measurement
DIRIS O-m - RS485 communication	
Link	RS485 2 … 3 half duplex wires
Protocol	Modbus RTU
Speed	1200 … 115200 bauds
Connection	Removable screw terminal, 3 positions, 0.14 to 1.5 mm² stranded or solid cable
DIRIS O-p - PROFIBUS communication	
Protocol	PROFIBUS DPV1

References

DIRIS B monitoring devices		Reference
DIRIS B-10	RS485 - Modbus - 230 VAC	4829 **0010**
DIRIS B-30	RS485 - Modbus - 230 VAC	4829 **0000**
DIRIS O optional modules		**Reference**
DIRIS O-iod	2 digital inputs / 2 digital outputs	4829 **0030**
DIRIS O-ioa	2 analogue inputs/2 analogue outputs 4-20 mA	4829 **0031**
DIRIS O-it	3 temperature inputs PT 100 / PT 1000	4829 **0032**
DIRIS O-m	RS485 Modbus communication	4829 **0033**
DIRIS O-p	PROFIBUS communication	4829 **0034**

Accessories	To be ordered in multiples of	Reference
DIRIS D-30 - Single-point display		4829 **0200**
RJ9 cable for DIRIS D-30 display - 1.5 m		4829 **0280**
RJ9 cable for DIRIS D-30 display - 3 m		4829 **0281**
DIRIS B sealing cover for I/O terminals		4829 **0049**
USB configuration cable		4829 **0050**
Fuse disconnect switches to protect voltage inputs (RM type)	4	5701 **0018**
Fuse disconnect switches to protect the 1-pole + neutral auxiliary power supply (RM type)	6	5701 **0017**
gG 10x38 0.5 A fuses	10	6012 **0000**