Specifications

Eaton 106424



Catalog Number: 106424

Eaton xEnergy Basic LV systems Low voltage switchgear. Glass door, for HxW=1760x600mm, left

General specifications

Product Name	**Catalog Number**
Eaton xEnergy Basic door	106424
EAN	**Product Length/Depth**
4015081061945	45 mm
Product Height	**Product Width**
1710 mm	615 mm
Product Weight	**Compliances**
16.9 kg	RoHS conform

Powering Business Worldwide

Product specifications

Used with

Floor-standing enclosure
Accessory
Accessory consideration
Service distribution board IVS

Special features

can be used as right door for two-leaf versions
order together with standard door for 600 mm
Protective cover mounted on left
Transparent doors
Two doors
Mounting from front, fast mounting, hinges on left or right possible
Door opening angle 167°
3-point turn lock with roller lever lock
Transparent panels from 4 mm safety glass (EN 12150-1, DIN 1249)

Type

Additional equipment for floor-standing service distribution board IVS

Features

EMC-version
Version as glazed door

Accessory/spare part type

Doors

Surface finishing

With powder coating
Powder coating

Color

Light gray (RAL 7035)
Gray

Degree of protection

IP30
NEMA Other

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

Unit type

Modular system

Suitable for height

1760 mm

Suitable for width

1200 mm

Cover/door color

Transparent

Cover/door type

Three-point turn-lock

Material

Steel

Sheet steel/glass

Housing material

Sheet steel/glass

Model

Stop door

Mounting method

Floor standing distribution board

Functions

Floor-standing enclosure

Additional equipment

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia