Cut protection

KRYTECH 380

Low risk - ISO B

Best cut protective glove for heavy duty work in oily environments



GRIP & PROOF TECHNOLOGY

CUT PROTECTION
LEVEL B

EN388	EN407	CATEGORY 2
4344B	X1XXXX	CE

ISO 13997:	DEXTERITY
7.6 N	EN ISO 21420: 5/5

SPECIFIC ADVANTAGES

Comfort

- Large cuff: Easy to put and remove - Reduction of RSI (musculoskeletal symptons) risks
- Large cuff and cotton inside: good perspiration management

Durability

- Longer service life: excellent mechanical resistance (abrasion, perforation)

Productivity

- Excellent grip for better productivity
- Grip and Proof coating ensures an excellent grip in very oily environment . It also reduces muscle strain and boosts productivity

Skin protection

- Skin protected on palm and knuckle in oily/wet conditions
- Free of harmful substances: DMF Free

Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

INDUSTRIES

- Automotive/mechanical industry
- Mechanical industry

APPLICATIONS

- Cutting and stamping metal
- Metal stamping in very oily environments
- Handling parts post-press
- Pressing metal, handling metal sheets

Edit 29/11/2024

Cut protection

KRYTECH 380

Low risk - ISO B

LEGENDS

EN388 MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

4	3	4	4	B	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)

X	1	X	X	X	X
0-4	0-4	0-4	0-4	0-4	0-4

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 0-4: Contact heat resistance
- X: Limited flame spread

PRODUCT DETAILS

Interior finish	Seamless textile support from HDPE and cotton fibres
Gauge	13
Exterior finish	Ventilated back
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Large safety cuff
Colour.s	Black Grey
European sizes	8 9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	8.6E+8 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	1.8E+8 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 6 pairs/bag 48 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/01/19/0327
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

Edit 29/11/2024