Rittal – The System.

Faster – better – everywhere.

VX SE free-standing enclosure system Stainless steel – SE 5850.600

Date : Jul 13, 2021

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

VX SE free-standing enclosure system Stainless steel – SE 5850.600

created: 13.07.2021 build on www.rittal.com/uk-en



Product description

Material:	Enclosure: Stainless steel 1.4301 (AISI 304), 1.5 mm, exterior brushed Door: Stainless steel 1.4301 (AISI 304), 2.0 mm, exterior brushed Rear panel: Stainless steel 1.4301 (AISI 304), 1.5 mm, exterior brushed Gland plates: Stainless steel 1.4301 (AISI 304), 1.5 mm Mounting plate: Sheet steel, 3.0 mm
Surface finish:	Enclosure, door and rear panel: Brushed, grain size 400 Gland plates: Uncoated Mounting plate: Zinc-plated
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	NEMA 12
IK Code:	IK10
Supply includes:	Enclosure, solid top and sides Door(s) R/h door hinge with single-door enclosures, may be swapped to opposite side Rear panel, detachable Mounting plate Gland plates Lock: 3 mm double-bit 2 punched rails 18 x 39 mm
Note:	Due to the hardness of the material, we recommend using metal multi-tooth screws 2486.400 for the interior installation.

Product description

Dimensions:	Width: 600 mm Height: 1600 mm Depth: 400 mm
Mounting plate:	Width: 499 mm Height: 1496 mm
Number of doors:	1
Packs of:	1 pc(s).
Weight/pack:	91.5 kg
EAN:	4028177959361
Customs tariff number:	94032080
ETIM 7.0:	EC000261
ETIM 6.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 6.0/6.1:	27180101
Product description:	VX SE Free-standing enclosure system, WHD: 600x1600x400 mm, Stainless Steel, 1.4301, with mounting plate, single door at the front

Approvals

Approvals:	UL + C-UL
Certificates:	Protection category
Declarations:	Declaration of conformity