TEGERA®





TEGERA® 7350

Learn more

KEEP THE HEAT AND THE GRIP

Super soft, winter lined nitrile glove for freezer rooms or outdoor use. The sandy finish gives a perfect grip on slippery tools. The chemical protection layer is 0,3 mm. The glove is waterproof, oil and grease resistant and approved for handling foodstuffs. It has a good fit and is warm and comfortable.

CHARACTERISTICS

- High level of protection
- Good fit
- Durable
- Good grip
- Warm
- Comfortable

FUNCTIONS

- Approved for handling foodstuffs
- Waterproof
- Protection against chemicals
- Latex-free
- Oil and grease resistant
- Water and oil repellent

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Corrosive injuries, contact with dirt, contact with chemicals, contact with damp, contact with oil and fat, contact with cold

PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, microbiological risk environments, environments hazardous to health, corrosive environments, cold environments, wet environments, moist environments, oily and greasy environments, dirty environments

PRIMARY AREAS OF USE

Painting, construction, concrete work, marine work, petro-chemical work, paper industry work, food handling, chemical work, chemical technology work

PRIMARY INDUSTRIES OF USE

Oil, gas, petrochemical, chemical

TYPE OF WORK

Medium weight

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

SPECIFICATION

TYPE Chemical protection gloves, Cold insulation gloves
CATEGORY Cat. III
THICKNESS 0,3* mm (*chem-layer)
LINING Winter-lined
LINING MATERIAL Fleece
LENGTH 300 mm
DEXTERITY 5
GRIP DESIGN Sandy finish
COLOUR Blue
PAIRS PER: BUNDLE/CARTON 5/60
AQL 1.5
DISPLAY TYPE Bag with euro slot
DIPPING MATERIAL Nitrile
INNER MATERIAL SPECIFICATION Acrylic
MIDDLE MATERIAL SPECIFICATION Cotton
OUTER MATERIAL SPECIFICATION Nitrile

COMPLIANCE

CE 2797

UKCA Cat. III

EAC

TP TC 019:2011

Information/UIS

EN ISO 374-1:2016/A1:2018 Type B
JKOPT

EN ISO 374-5:2016

EN 388:2016+A1:2018
3121X

EN ISO 21420:2020

FEATURES

Warm lining

Windproof

Waterproof

Chemical protection

TEST ACCORDING TO EN ISO 374-1:2016

Tested chemical	J	K	O	P	T
Permeation level	6	6	2	5	6
Degradation %	1,96	9,16	3,98	10,85	3,01

SIZE		ARTICLE NUMBER	EAN
8	M	7350-8	7392626013025
9	L	7350-9	7392626059528
10	XL	7350-10	7392626013032
11	XXL	7350-11	7392626035560

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.