Date: 17/04/2023

TR11-C, 1xPt100, 3-w, Cl.B, -50/250°C (F), terminal block, Not removable

TR11-C RTD assembly with fabricated threaded protection tube (tubing)

Item number:	45280011
Quantity:	1 pcs.
Order code:	TR11-C-ZZZZ-13DR-BS1A-ZZ-ATGGDL90150ZZZ00178-ZZZZR12 ZZZZZZZZ-ZA-Z-WIKA0-ZZ
Overview:	TR11-C, 1xPt100, 3-w, Cl.B, -50/250°C (F), terminal block, Not removable Head / housing: BS (Alu), Strd.-gland, M20 x 1.5 Transmitter: Without (terminal block) Protection tube: Straight, thread 316L, Ø 6x1 mm, M24 x 1,5 - G1/2B, MH=Without U1=150mm Sealing: Without Specifications according to data sheet: TE 60.03 Protection tube total length (spare) [L]: 178 mm Thermowell specials: Without
Details:	TR11-C RTD assembly with fabricated threaded protection tube (tubing) Specifications according to data sheet: TE 60.03 1xPt100, 3-wire Class B, IEC 60751 Temperature range of selected class: -50...+250°C, Sensor: Thin film BS, Aluminum, flat cover Cable entry: Standard cable entry Thread size cable entry: M20 x 1.5 Transmitter: Without (terminal block) Protection tube: Straight, thread Connection to neck tube: M24 x 1,5 Protection tube diameter: 6x1 mm Protection tube material: Stainless steel 316L Process connection: G 1/2 B Insertion length [U1]: 100 mm Neck length [MH/N] (mm): Without Sealing: Without Measuring insert: Not removable (no measuring insert) Thermowell specials: Without TR11-C RTD assembly with fabricated threaded protection tube (tubing)

© 2023 - WIKA Instruments s.a.r.l.

Specifications according to data sheet: TE 60.03
1xPt100, 3-wire
Class B, IEC 60751
Temperature range of selected class: -50...+250°C
BS, Aluminum, flat cover
Cable entry: Standard cable entry
Thread size cable entry: M20 x 1.5
Transmitter: Without (terminal block)
Protection tube: Straight, thread
Connection to neck tube: M24 x 1,5
Protection tube diameter: 6x1 mm
Protection tube material: Stainless steel 316L
Process connection: G 1/2 B
Insertion length [A] [U1]: 150 mm
Neck length [MH/N]: Without
Sealing: Without
Measuring insert: Not removable (no measuring insert)
Thermowell specials: Without

© 2023 - WIKA Instruments s.a.r.l.