Laserliner

Duraplane G360 Set 175 cm



Robust horizontal 360° line laser with anti-drift system





- Duraplane G360:
- Extremely bright 360° line laser
- Automatic Level: horizontal self-levelling through magnetically damped pendulum system
- ADS tilt: Auto power off in the event of external influence through ADS
- Slopefunction
- Robust, dustproof and waterproof (IP 54)
- Operating time doubled due to 2 Li-Ion batteries
- 2 brightness levels
- RX-Ready: integrated handheld receiver mode
- RangeXtender G 60:
- Detection of the laser lines up to max. 60 m
- High-Speed: very fast detection of laser lines
- Head magnet
- Universal mount
- Compact Tripod 175 cm:
- Crank tripod of aluminium
- Telescopic levelling staff 3 m:
- Easy-to-read, highly stable levelling staffs for use even under extreme conditions
- Made of a durable aluminium profile

TECHNICAL SPECIFICATIONS

SELF-LEVELLING RANGE	± 3.5° (horizontal)
ACCURACY	± 0.2 mm / m
LEVELLING	horizontal automatic
VISIBILITY (TYPICAL)*	60 m
LUX	at max. 300 lux
WORKING RANGE WITH HAND RECEIVER	(depends on how the technology affects the difference in brightness) 60 m
LASER WAVELENGTH	515 nm
LASER CLASS	2 / < 1 mW (EN 60825-1:2014/AC:2017)
POWER SUPPLY	Li-ion battery pack 7.4V / 2.6Ah Power supply 12V/DC / 2000mAh
OPERATING TIME	approx. 10 hours
OPERATING CONDITIONS	0°C … 50°C, max. humidity 80% rH, no condensation, max. working altitude 4000 m above sea level
STORAGE CONDITIONS	-10°C … 70°C, max. humidity 80% rH
DIMENSIONS (W X H X D)	125 mm x 145 mm x 120 mm
WEIGHT	812 g (incl. battery pack / without accessories)







Duraplane G360 Set 175 cm	**ORDER NO.** 052.555A	**EAN-CODE** 4021563710515	**PU** 1

UMAREX GmbH & Co. KG • Donnerfeld 2 • 59757 Arnsberg • Germany • Tel. +49 2932 638-300 • Fax +49 2932 638-333 • info@laserliner.com • www.laserliner.com