PRODUCT-DETAILS

E6.2H 4000 Ekip Touch LSIG 4p F HR

E6.2H 4000 Ekip Touch LSIG 4p F HR



General Information

Extended Product Type	E6.2H 4000 Ekip Touch LSIG 4p F HR
Product ID	1SDA071866R1
EAN	8015644757168
Catalog Description	E6.2H 4000 Ekip Touch LSIG 4p F HR
Long Description	C.BREAKER EMAX2 E6.2H 4000 FIXED FOUR-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/TOUCH-LSIG R 4000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions

ABB EcoSolutions	Yes
Environmental Product Declaration - EPD	9AKK108468A1905 9AKK108468A1913

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424

© 2024 ABB. All rights reserved.

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	fd46707c-ec22-4722-add4-bcb6e8c4368b Italy (IT)
Simplified SCIP	9a51ada7-9a75-4c66-9e4f-825aedd81198 Germany (DE) 55234862-09fd-4d70-ae07-66606b210685 Germany (DE) 870ddeca-f958-425b-89e8-8145feab45d0 Sweden (SE) 383e2b14-b95e-46cb-8105-c5c42a5a126a Poland (PL) 01c1335e-f6fa-4ba0-b379-950f145c7c7c Czech Republic (CZ) 27f75f29-1d87-472e-8ca1-ab13a9251379 Poland (PL) 434b54ab-5ecd-4192-9674-e67912e836a1 Norway (NO) 790da2ee-063c-4cba-a3de-4d47423b75ff France (FR) ada25cdc-2025-41df-96eb-482a12ae9c8a Finland (FI) 74e5f84b-9bf1-4fde-b1f7-bfc4e1fe741d Belgium (BE) 583fddd4-9038-44ad-8cd8-24c0a95dd61b Croatia (HR) e0e7cc62-624e-42d2-a6ee-6bf101452f38 Hungary (HU) 2833cd64-35d5-482d-ae2a-dca30fdedfce Estonia (EE) ab69e476-9a22-4429-b88c-939212121692 Denmark (DK) b47e87f8-9f84-4aea-b627-4b3e1becdf93 Greece (GR) 67aedbbc-627e-47a8-a10d-0018287b9d41 Germany (DE) b14eaab5-0517-46d1-b529-5b04f3b8c878 France (FR) 7de56b2a-4e6b-4be1-aa1b-11f58c896644 Germany (DE) 9f884bc5-824a-411b-a5dd-ad71f888ee62 Sweden (SE) adb0dd0f-97f2-4545-b964-743649b29126 Netherlands (NL) dcc56d8b-b77d-4ea3-9782-5d05a6250871 Poland (PL) 60f356f3-ae3a-4b1a-9610-32e9f8acaab4 Belgium (BE) 647c3eff-ba06-4781-943d-8cd320807c62 Spain (ES) 91c6a20b-bdf8-452d-8365-79f777dfd308 Germany (DE) 836fcfcf-ec6d-4957-ad90-e7496212a58b Hungary (HU) 13e2ae2a-57da-45ae-be85-b967cf46f671 Portugal (PT) 6c7ad957-1730-4e71-9e11-ec594f3df679 Bulgaria (BG)

Environmental

Environmental Information	9AKK108467A6707

Ordering

Order Code US and Canada	ZDHWERBF000A000000XX
EAN	8015644757168
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	888 mm
Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	125 kg

Container Information

Package Level 1 Units	box 1 piece

© 2024 ABB. All rights reserved.

Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	1127 mm
Package Level 1 Gross Weight	134 kg
Package Level 1 EAN	8015644757168

Additional Information

Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	F
CAD Dimensional Drawing	1SDH001252R0249

Technical

Current Type	AC
Electrical Durability	Ue =< 440 V 4000 cycle Ue = 500 ... 690 V 4000 cycle 10 cycles per hour
Mechanical Durability	12000 cycle 60 cycles per hour
Neutral Pole Current ([% Iu])	50 %
Number of Poles	4P
Power Loss	309 W
Rated Current (I_n)	4000 A
Rated Impulse Withstand Voltage (U_{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U_i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 100 kA (500 V AC) 100 kA (660 V AC) 100 kA (690 V AC) 100 kA
Rated Service Short-Circuit Breaking Capacity, in % of Icu (I_{cs})	100 %
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 100 kA for 3 s 100 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 100 kA (500 V AC) 100 kA (525 V AC) 100 kA (690 V AC) 100 kA
Rated Uninterrupted Current (I_u)	4000 A

© 2024 ABB. All rights reserved.

Rated Voltage (U_r)	690 V
Recommended Screw Driver	Main Circuit M12
Release	Ekip Touch LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	IEC
Sub-type	E6.2
Suitable for IT Networks	Yes, 690V
Terminal Connection Type	Rear flat Horizontal
Terminal Type	Bolt
Tightening Torque	70 N·m

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5544
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH001060R0100
Wiring Diagram	1SDM000091R0001
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

© 2024 ABB. All rights reserved.

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2



© 2024 ABB. All rights reserved.