Product data sheet
Characteristics

ZCKE676
limit switch head ZCKE - steel roller plunger reinforced - -40 °C



Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJ2H29 ZCKJ8H7 ZCKJ7H29 ZCKJD31 ZCKJD37H7 ZCKJD31H7 ZCKJ6H29 ZCKJ6H7 ZCKJ4H7 ZCKJ6 ZCKJ5H29 ZCKJ9H7 ZCKJ1H29 ZCKJ1H7 ZCKJ9H29 ZCKJ41H7 ZCKJ2H7 ZCKJ41H29 ZCKJ4 ZCKJD39H7 ZCKJ4H29 ZCKJD31H29 ZCKJD35H29 ZCKJ5H7 ZCKJ41 ZCKJD35H7 ZCKJ5 ZCKJD37H29 ZCKJ7 ZCKJD39H29 ZCKJD35

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	ZCKJ8 ZCKJD37 ZCKJ21H29 ZCKJ7H7 ZCKJ21H7 ZCKJ21 ZCKJD39 ZCKJ9 ZCKJ8H29 ZCKJ11H29 ZCKJ11H7 ZCKJ1 ZCKJ2 ZCKJ11
Movement of operating head	Linear
Type of operator	Roller plunger spring return metal (reinforced)
Type of approach	Lateral approach, 2 directions

Complementary

Switch actuation	By 30° cam
Positive opening	With
Net weight	0.155 kg
Head material	Metal

Environment

Ambient air temperature for operation	-40…70 °C
Ambient air temperature for storage	-40…70 °C
Environmental characteristic	Low temperature

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months