Rittal – The System.

Faster – better – everywhere.

EMC cable glands – SZ 2843.500

Date : Apr 26, 2021

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

EMC cable glands – SZ 2843.500

created: 26.04.2021 build on www.rittal.com/uk-en



Product description

Design:	Cable glands, metric
Description:	The cable sheathing may optionally be interrupted at the contact point or removed completely inside the enclosure. The cable shielding in the enclosure is retained. The supplied lock nut cuts automatically into the paint when screwed onto spray-finished enclosure surfaces, thus creating a conductive connection.
Protection category IP to IEC 60 529:	IP 68
Protection category IP to DIN 40 050-9:	IP 69K
Note:	Minimum shield diameter = cable diameter less cable sheathing

Product description

Shield diameter (min.):	19 mm
Min. cable diameter:	27 mm
Max. cable diameter:	38 mm
Cable entry:	Metric diameter: M50
Packs of:	1 pc(s).
Weight/pack:	0.34 kg
Copper weight (kg	0

per piece):	
EAN:	4028177247062
Customs tariff number:	73269098
ETIM 7.0:	EC000441
ETIM 6.0:	EC000441
eCl@ss 8.0/8.1:	27149109
eCl@ss 6.0/6.1:	27189214
Product description:	SZ EMC cable glands, metric, size: M50

Approvals

Approvals:	UL + C-UL VDE
Certificates:	NA
Declarations:	Declaration of conformity