Date: 11/04/2023

TR34, 4...20mA, Without, 75 mm x 6 mm

TR34 Miniature resistance thermometer, explosion protected version, thread-mounted

Item number:	48787586		
Quantity:	1 pcs.		
Order code:	TR34-B-TT-CL1100-ZZ60075-ZZZ-FZZ-ZZZ	R34	0085CW0000WIKA0Z
Overview:	TR34, 4...20mA, Without, 75 mm x 6 mm		

ATEX / IECEx
Output signal: 4...20mA -10°C 100°C
Electrical connection: Circular connector, M12x1

Process connection: Without
Process temperature: -30 ... +150°C
Sensor diameter ød: 6 mm
Insertion length A: 75 mm
Permissible ambient temperature: -40 ... +85 °C (-40 ... +185 °F)
Pin assignment: 1+ (10..30VDC) und 3- (0V)
Transmitter damping: Standard

Specifications according to data sheet: TE 60.34

Details: TR34 Miniature resistance thermometer, explosion protected version, thread-mounted

Specifications according to data sheet: TE 60.34
Electrical connection: Circular connector, M12x1
Approvals: ATEX / IECEx
Output signal: 4…20mA, 2-wire
Transmitter Unit: °C
Process temperature: -30 ... +150°C
Transmitter initial value: -10°C
Transmitter final value: 100°C
Process connection: Without
Sensor diameter ød: 6 mm
Insertion length A: 75 mm
Permissible ambient temperature: -40 ... +85 °C (-40 ... +185 °F)
Pin assignment: Standard pin connection 1+ (10..30VDC) and 3- (0V)
Transmitter damping: Standard

© 2023 - WIKA Instruments s.a.r.l.