Date: 22/04/2024

PCA2PG 3 … 25 bar 1/4 NPT-F , Adaptor M20x1,5-F

Compact pressure switch, flameproof Enclosure Ex d

Item number: 48751936

Quantity: 1 pcs.

Order code: PCA2PG-BAOB-1ISZZZ1ZZ CZKW
F4-C5- - - - -

Overview:
PCA2PG 3 … 25 bar 1/4 NPT-F , Adaptor M20x1,5-F
Compact pressure switch, flameproof Enclosure Ex d PCA
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Piston Stainless Steel 316, O-Ring FPM
Connection: Stainless steel AISI 316L
contact version: 1xDPDT, silver contact
3 … 25 bar, working range 0 … 250 bar, proof pressure 400 bar
Set point definition: Set Point not defined
Process connection: 1/4 NPT-F
Electrical connection: Adaptor M20x1,5-F
standard direct or wall mounting, fixing bore on the case
Ingress Protection: IP66
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 33.31
Repeatability of set point: ≤ 1% of end of setting range

Details:
Compact pressure switch, flameproof Enclosure Ex d
Model PCA
Specifications according to data sheet: PV 33.31
Repeatability of set point: ≤ 1% of end of setting range
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Piston Stainless Steel 316, O-Ring FPM
1xDPDT, silver contact
3 … 25 bar, working range 0 … 250 bar, proof pressure 400 bar
Set Point not defined
Process connection: 1/4 NPT-F
Electrical connection: Adaptor M20x1,5-F
standard direct or wall mounting, fixing bore on the case
Approvals / Certificates: with
Brand: WIKA Instruments Italia
Ingress Protection: IP66
PCA2PG 3 … 25 bar

© 2024 - WIKA Instruments s.a.r.l.