Date: 11/04/2023

DCMH2A - 0...6 bar - Adaptor G 1/4 A-M - 2x1/2 -14 NPT-F

Compact differential pressure switch

Item number: 48790085

Quantity: 1 pcs.

Order code: DCMH2A-BBI C-5LMZZZABZ1Z ZCW
B000050DZZZZZZZZZ
CERT31-EN2C-FC- - - - - UZZ

Overview: DCMH2A - 0...6 bar - Adaptor G 1/4 A-M - 2x1/2 -14 NPT-F
Compact differential pressure switch DC
static and one-side pressure: 100 bar
switch enclosure: aluminium,copper-free
contact version: 1xSPDT, silver contact
setting range: 0...6 bar
Set point definition: Set Point customer-specifically configured
Process connection: Adaptor G 1/4 A-M
Electrical connection: 2x1/2 -14 NPT-F
Mounting: Enclosure with plate for wall or direct mounting
Diaphragm Material: AISI 304
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 35.40
Repeatability of set point: ≤ 1% of span
Connection: Stainless steel AISI 316L

1. set point: 0.50 bar decreasing,

Inspection certificate acc. to EN 10204 3.1
Certificate Language: English
Inspection: 100% Inspection (with calibration values listed each instrument)

Details: Compact differential pressure switch
Model DC
Specifications according to data sheet: PV 35.40
Repeatability of set point: ≤ 1% of span
static and one-side pressure: 100 bar
Model of Differential Cell: H, for setting ranges from 400 mbar to 25 bar
switch enclosure: aluminium,copper-free
contact version: 1xSPDT, silver contact
Unit: bar
setting range: 0...6 bar
Process connection: Adaptor G 1/4 A-M
Electrical connection: 2x1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting

© 2023 - WIKA Instruments s.a.r.l.

Diaphragm Material: AISI 304
Set point definition: Set Point customer-specifically configured
Brand: WIKA Instruments Italia
Connection: Stainless steel AISI 316L
DCMH2A
1. set point: 0.50 bar decreasing,

Inspection certificate acc. to EN 10204 3.1
Certificate Language: English
Inspection: 100% Inspection (with calibration values listed each instrument)

© 2023 - WIKA Instruments s.a.r.l.