Rittal – The System.

Faster – better – everywhere.

Enclosure heater without fan – SK 3105.330

Date : Mar 21, 2019

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Enclosure heater without fan – SK 3105.330

created: 21.03.2019 on www.rittal.com/com-en



Product description

Supply includes:	PTC heater Quick-connection terminal Assembly parts
Note:	For precise temperature control inside the enclosure, we recommend the enclosure internal thermostat or the digital enclosure internal temperature display and thermostat. In order to prevent condensation on assemblies, a hygrostat is recommended to regulate heating. In larger enclosures, even heat distribution is best achieved by installing several low-output heaters. The installation of heaters is generally advisable, in order to prevent condensation.
Note on Model No.:	Special voltages available on request. We reserve the right to make technical modifications.

Product features

Continuous thermal output at 10 °C:	23 W - 30 W
Rated operating voltage:	110 V - 240 V, 1~, 50 Hz/60 Hz
Dimensions:	Width: 64 mm Height: 155 mm Depth: 56 mm
Miniature circuit-breaker/fuse:	4 A
Packs of:	1 pc(s).
Weight/pack:	0.38 kg

© Rittal 2019

EAN:	4028177638631
Customs tariff number:	85162999
ETIM 6.0:	EC000737
ETIM 5.0:	EC000737
eCl@ss 8.0/8.1:	27180710
eCl@ss 7.0/7.1:	27180710
eCl@ss 6.0/6.1:	27180710
eCl@ss 5.1/5.1.4:	27180710
Product description:	SK enclosure heater, without fan, 23-30 W, 110-240 V, 1~, 50/60 Hz, WHD: 64 x 155 x 56 mm

Approvals

Approvals:	Approval overview CSA UR + C-UR VDE
Certificates:	EAC
Declarations:	Declaration of conformity

© Rittal 2019