professionalLINE 360° LED Construction Light TU 23051 M FR 23700lm+3200lm, IP54, 5 m H07RN-F 3G1,5 *FR*



Technical data

Product number:	9171421100
EAN:	3281854211003
Luminous flux:	23,700 lm
Total luminous flux secondary source:	3,200 lm
Power consumption:	190 W
Luminous efficacy:	125 lm/W
Energy efficiency class:	E

Colour temperature:	6,500 K
Colour rendering index CRI:	88
Min.-Max. Nominal input voltage:	220V - 240V
Lifetime:	30,000 h
Cable length:	5 m
Cable designation:	H07RN-F 3G1,5
Max. height adjustable:	1.73 cm
With socket outlet:	Yes
Number of socket outlets:	2
Impact strength:	IK08
Protection class:	I
Degree of protection (IP):	IP54
Colour:	black, orange

Product texts

For indoors and outdoors use, IP54, IK08.

* Excellent all-round illumination thanks to 360° beam angle, glare-free light and large light diffusion.
* With additional extendable, tiltable and swivelling spot Telescope lockable and extendable up to approx. 1,73 m.
* All-terrain, transportable spotlight with wheel brake.
* Both lights can be switched independently.
* With dimming function: 100% / 50% / 25%.
* Robust, break-proof and impact-resistant plastic housing.
* Category 2 (K2) equipment: for use in harsh environments with high mechanical, physical and chemical impact.