Thermal protection

# TEMPICE 700

Temperature to -10°C | Wet environments

## Reinforced Durability to push the limits of cold




GRIP & PROOF TECHNOLOGY

EN388

3222X

EN 511:2006

02X

DEXTERITY

EN420:
5/5

CATEGORY 2

CE

## SPECIFIC ADVANTAGES

### Comfort

- Stay dry when working in wet conditions

### Durability

- Coating 5 times as durable than standard gloves on the market

### Productivity

- Excellent grip when handling wet parts
- Grip and Proof coating ensures an excellent grip in very oily environment . It also reduces muscle strain and boosts productivity

### Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

### Washability

- Washable up to 5 times at 60°C , allowing to extend glove lifespan, reduce costs and waste.

## INDUSTRIES

- Local Authorities (Catering Services)
- Local Authorities (Roads and Highways)
- Local Authorities (Parks and Public Spaces)
- Local Authorities (Waste Collection and Processing)
- Other industries
- Transport, logistics

## APPLICATIONS

- Maintaining the roads
- Public park maintenance
- Waste collection
- Construction materials handling
- Maintenance in wet or cold environments
- Order preparation

Edit 18/03/2024

Thermal protection

# TEMPICE 700

Temperature to -10°C | Wet environments

## LEGENDS

EN388 MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

| 3 | 2 | 2 | 2 | X | |
|---|---|---|---|---|---|
| 0-4 | 0-5 | 0-4 | 0-4 | A-F | P |

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN 511:2006 COLD HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

| 0 | 2 | X |
|---|---|---|
| 0-4 | 0-4 | 0/1 |

- 0/1: Water permeability
- 0-4: Contact cold resistance
- 0-4: Convective cold resistance

## PRODUCT DETAILS

| | |
|---|---|
| Interior finish | Knitted thermal protection |
| Gauge | 10 |
| Exterior finish | Non-slip grip |
| Material | Nitrile GRIP&PROOF coating |
| Cuff characteristic | Knitted Cuff |
| Colour.s | Black Blue |
| European sizes | 7 8 9 10 |
| Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity) | 7.6E+9 Ω |
| Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity) | 3.5E+11 Ω |

## LOGISTIC DETAILS

| | |
|---|---|
| Packaging | 1 pair/bag<br>12 pairs/bag<br>72 pairs/carton |

## LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1671
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

Edit 18/03/2024