Rittal – The System.

Faster – better – everywhere.

Outdoor wall-mounted enclosures – CS 9791.035

Date : Apr 27, 2021

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Outdoor wall-mounted enclosures – CS 9791.035

created: 27.04.2021 build on www.rittal.com/uk-en



Product description

Description:	Outdoor enclosures for wall or pole mounting. Enclosure-within-an-enclosure concept, outer enclosure with cut-out in the bottom and integrated louvres on the rear panel and side panels for ventilation.
Material:	Enclosure and mounting plate: Aluminium, AlMg3 Door, inner enclosure: Stainless steel 1.4301 (AISI 304)
Surface finish:	Enclosure: Powder-coated, UV-resistant pure polyester
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Supply includes:	Double-walled outdoor enclosure, fully preconfigured Inner enclosure with mounting plate, gland plate and security lock Mounting bracket for enclosure internal thermostat or hygrostat Outer enclosure with designer cover and security lock 3524 E 2 C rails on the rear panel
Note:	Extended delivery times.
Basic material:	Aluminium

Product description

Dimensions:	Width: 530 mm Height: 700 mm Depth: 265 mm
Clearances:	Clearance width: 440 mm

	Clearance height: 545 mm Clearance depth: 195 mm
Mounting plate:	Width: 430 mm Height: 535 mm
Inner enclosure:	Width: 460 mm Height: 565 mm Depth: 220 mm
Lock version:	Cam
Number of locks:	2
Packs of:	1 pc(s).
Weight/pack:	14.86 kg
EAN:	4028177193710
Customs tariff number:	94032080
ETIM 7.0:	EC000261
ETIM 6.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 6.0/6.1:	27180101
Product description:	CS Wall-mounted enclosure, WHD: 530x700x265 mm, aluminum, with mounting plate, Enclosure-within-an-enclosure concept

Approvals

Declarations:	Declaration of conformity