Specifications

Eaton 260140

Catalog Number: 260140

Eaton Moeller series NZM - Molded Case Circuit Breaker. Rotary handle, red-yellow, lockable, size 3



General specifications

Product Name
Eaton Moeller series NZM operating element

Catalog Number
260140

EAN
4015082601409

Product Length/Depth
108 mm

Product Height
124 mm

Product Width
140 mm

Product Weight
0.854 kg

Compliances
UL/CSA
IEC
RoHS conform

Certifications
UL489
CSA (File No. 22086)
CSA-C22.2 No. 5-09
CSA (Class No. 1437-01)
UL listed
UL (Category Control Number DIHS)
CE marking
CSA certified
UL (File No. E140305)
IEC60947

Powering Business Worldwide

Product specifications

Used with

NZM3(-4), PN3(-4), N(S)3(-4)

Type

Accessory
Rotary handle on circuit-breaker

Special features

Complete with rotary drive
Can be combined with insulating surround
MODAN handle position detection by wire release can be retrofitted
Makes it possible to operate the switch with a rotational movement and provides locking facilities

Features

Red-yellow for emergency switching off
Lockable

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to

Resources

Brochures

eaton-digital-nzm-brochure-br013003en-en-us.pdf

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM3

Drawings

eaton-circuit-breaker-rotary-handle-nzm-rotary-handle-dimensions-003.eps

eaton-circuit-breaker-padlock-nzm-rotary-handle-dimensions.eps

eaton-circuit-breaker-rotary-handle-nzm-rotary-handle-3d-drawing-005.eps

Installation instructions

eaton-circuit-breakers-rotary-drive-nzm3-xd-v-kl-instruction-leaflet-il01219014z.pdf

Installation videos

The new digital NZM Range

Introduction of the new digital circuit breaker NZM

mCAD model

DA-CS-nzm3_xd

DA-CD-nzm3_xd

Technical data sheets

eaton-nzm-technical-information-sheet

normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Color

Red

Fitted with:

Padlock

Frame

NZM3

Activation type

Rotary handle

Suitable for

Power circuit breaker

Switch disconnector

Emergency stop

Locking facility

Lockable on the 0 position on the switch using up to 3 padlocks

Degree of protection / NEMA enclosure type

IP20

4X. 12

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia