PRODUCT-DETAILS

# SU203M-Z5

## SU203M-Z5 Miniature Circuit Breaker - 3P - Z - 5 A



### General Information

| | |
|---|---|
| Extended Product Type | SU203M-Z5 |
| Product ID | 2CDS273337R0358 |
| EAN | 4016779933360 |
| Catalog Description | SU203M-Z5 Miniature Circuit Breaker - 3P - Z - 5 A |
| Long Description | SU203M-Z5 Miniature Circuit Breaker Z-Char., 10kA, 5A, 3P UL489 |

### Technical

| | |
|---|---|
| Standards | CSA 22.2 No. 5<br>IEC/EN 60947-2<br>UL 489 |
| Tripping Characteristic | Z |
| Rated Operational Voltage | acc. to IEC 60898-1 400 V AC<br>acc. to IEC 60898-1 400 V<br>acc. to IEC 60947-2 400 V AC |
| Rated Insulation Voltage ($U_i$) | acc. to IEC/EN 60664-1 440 V |
| Rated Impulse Withstand Voltage ($U_{imp}$ | 4 kV<br>at 2000 m 5 kV |

© 2024 ABB. All rights reserved.

| | |
|---|---|
| ) | at Sea Level 6.2 kV |
| Dielectric Test Voltage | 50/60 Hz, 1 min: 2 kV |
| Input Voltage Type | AC/DC |
| Rated Current ($I_n$) | 5 A |
| Rated Short-Circuit Capacity | (400 V AC) 11.2 kA |
| Rated Ultimate Short-Circuit Breaking Capacity ($I_{cu}$) | (400 V AC) 15 kA<br>(400 V) 15 kA |
| Rated Conditional Short-Circuit Current ($I_{nc}$) | (400 V) 15 kA |
| Rated Service Short-Circuit Breaking Capacity ($I_{cs}$) | (400 V AC) 11.2 kA |
| Rated Frequency (f) | 50 / 60 Hz<br>DC |
| Power Loss | 5.4 W<br>at Rated Operating Conditions per Pole 1.8 W |
| Power Supply Connection | Arbitrary |
| Contact Position Indication | Red ON / Green OFF |
| Energy Limiting Class | 3 |
| Electrical Endurance | 20000 AC cycle |
| Mechanical Endurance | 20000 cycle |
| Number of Protected Poles | 3 |
| Number of Poles | 3 |
| Overvoltage Category | III |
| Tightening Torque | 2.8 N·m |
| Screw Terminal Type | Failsafe Bi-directional Cylinder-lift Terminal |
| Actuator Marking | I / O |
| Actuator Material | Insulation Group II, Black, Sealable |
| Housing Material | Insulation Group I, RAL 7035 |
| Mounting on DIN Rail | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 |
| Mounting Position | any |
| Recommended Screw Driver | Pozidriv 2 |
| Accessories Available | Yes |
| Connecting Capacity | Busbar 10 / 10 mm²<br>Flexible with Ferrule 0.75 ... 25 mm²<br>Flexible 0.75 ... 25 mm²<br>Flexible 0.75 ... 25 mm²<br>Rigid 0.75 ... 35 mm²<br>Stranded 0.75 ... 35 mm² |
| Installation Size | acc. to DIN 43880 3 |
| Terminal Type | Double Clamp |

## Material Compliance

| | |
|---|---|
| RoHS Information | 2CDK400595D2705 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date | 20200514 |
| REACH Declaration | 9AKK108468A9644 |
| REACH Information | True - contains substances > 0.1 mass percentage |
| REACH Date | 20231212 |
| Conflict Minerals | 9AKK108468A3363 |

© 2024 ABB. All rights reserved.

Subject to change without notice

| | |
|---|---|
| Reporting Template (CMRT) | |
| SCIP | 89318623-ff2d-4ce0-aefe-5d16fac11138 Germany (DE) |

## Environmental

| | |
|---|---|
| Ambient Air Temperature | Operation -25 ... +55 °C<br>Storage -40 ... +70 °C |
| Reference Ambient Air Temperature | 30 °C |
| Degree of Protection | IP20<br>IP40<br>Enclosure with Cover IP40 |
| Pollution Degree | 3 |
| Environmental Conditions | 28 cycles<br>with 55 °C / 90-96 %<br>and 25 °C / 95-100 % |
| Resistance to Vibrations | 20 Cycles with Load 0.8 In: 5g 5 ... 150 ... 5 Hz |
| Resistance to Shock acc. to IEC 60068-2-27 | 25g 2 shocks 13 ms |
| Environmental Information | 9AKK107680A9140 |

## Technical UL/CSA

| | |
|---|---|
| Maximum Operating Voltage UL/CSA | 480Y / 277 V AC |
| Interrupting Rating acc. to UL489 | (240 V AC) 10 kA<br>(480Y / 277 V AC) 10 kA |
| Connecting Capacity UL/CSA | Busbar 18-8 AWG<br>Conductor 18-4 AWG |

## Dimensions

| | |
|---|---|
| Width in Number of Modular Spacings | 3.0 |
| Product Net Width | 52.5 mm |
| Product Net Height | 111 mm |
| Product Net Depth / Length | 69 mm |
| Product Net Weight | 0.375 kg |
| Pole Net Weight | 0.125 kg |
| Built-In Depth ($t_2$) | 69 mm |

## Ordering

| | |
|---|---|
| Package Level 1 Units | carton 1 piece |
| Package Level 1 Gross Weight | 0.4 kg |

## Certificates and Declarations

| | |
|---|---|
| Certification Agency | CSA<br>EN<br>IEC<br>UL |

© 2024 ABB. All rights reserved.

| | |
|---|---|
| Declaration of Conformity - CE | 2CDK400595D2705 |
| Declaration of Conformity - UKCA | 9AKK108467A5201 |

## Installation

| | |
|---|---|
| Instructions and Manuals | 2CDC002177D0202 |

## Popular Downloads

| | |
|---|---|
| Data Sheet, Technical Information | 2CDC002177D0202 |

## Classifications

| | |
|---|---|
| ETIM 8 | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 9 | EC000042 - Miniature circuit breaker (MCB) |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Business |
| CN8 | 8536 20 10 |
| UNSPSC | 39121603 |
| eClass | V11.0 : 27141901 |
| IDEA Granular Category Code (IGCC) | 4899 >> Miniature circuit breaker (MCB) screw-in model |

## Accessories

| Identifier | Description | Type | Quantity | Unit Of Measure |
|---|---|---|---|---|
| 2CCA880100R0001 | CMS-100PS Sensor | CMS-100PS | 1 | piece |
| 2CCA880101R0001 | CMS-101PS Sensor | CMS-101PS | 1 | piece |
| 2CCA880102R0001 | CMS-102PS Sensor | CMS-102PS | 1 | piece |
| 2CDS200914R0001 | S2C-H6RU Auxiliary Contact | S2C-H6RU | 1 | piece |
| 2CDS200924R0001 | S2C-S6RU Signal / Auxiliary Contact | S2C-S6RU | 1 | piece |
| 2CDS200908R0001 | S2C-A1U Shunt Trip | S2C-A1U | 1 | piece |
| 2CDS200908R0002 | S2C-A2U Shunt Trip | S2C-A2U | 1 | piece |

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs

© 2024 ABB. All rights reserved.







© 2024 ABB. All rights reserved.