Specifications

Eaton 260015



Catalog Number: 260015

Eaton Moeller series NZM - Molded Case Circuit Breaker. Box terminal, 3p, up to 160 A, 1

General specifications

Product Name
Eaton Moeller series NZM connection type

Catalog Number
260015

EAN
4015082600150

Product Length/Depth
13 mm

Product Height
24.5 mm

Product Width
16.6 mm

Product Weight
0.078 kg

Compliances
IEC
UL/CSA
RoHS conform

Certifications
UL489
UL listed
CSA (Class No. 1437-01)
CSA (File No. 22086)
CSA-C22.2 No. 5-09
IEC60947
UL (Category Control Number DIHS)
CE marking
CSA certified
UL (File No. E31593)

Powering Business Worldwide

Product specifications

Used with

NZM1(-4), PN1(-4), N(S)1(-4)

Type

Accessory
Box terminal

Amperage Rating

160 A

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be

Resources

Brochures

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

eaton-digital-nzm-brochure-br013003en-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM1

Installation instructions

eaton-cirucit-breaker-switch-disconnector-nzmb-il01203004z.pdf

Installation videos

The new digital NZM Range

Introduction of the new digital circuit breaker NZM

mCAD model

nzm1_xkc

nzm1_xkc.stp

Technical data sheets

eaton-nzm-technical-information-sheet

evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Frame

NZM1

Suitable for

Three-pole

Copper cable

Number of poles

Three-pole

Terminal capacity (copper strip)

2 segments of 9 mm x 0.8 mm - 9 segments of 9 mm x 0.8 mm

Model

Other

Terminal capacity (stranded cable)

6 mm² - 25 mm² (2x)

10 mm² - 70 mm² (1x)

12 - 2/0 AWG/kcmil (1x)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia