Polyurethane spiral hoses with non-scratching fittings

Polyurethane recoils with rigid and swiveling male fittings



Technical characteristics

- **Max operating pressure:** 8 bar
- **Temperature:** -15°C to +70°C
- **Construction:** Polyurethane
- **Highlight:** Non scratch
- **Equipped with:** Teflon-coated coupler

Black

BSPT male thread	ID/OD (mm)	Coil Ø (mm)	Max length (m)	Min. length (m)	Parts Numbers
R 1/4	6.5 x 10	42	4	0.4	**PUS 64NR**
R 1/4	6.5 x 10	52	6	0.63	**PUS 66NR**

PREVOST UK - G, Tower Business Park, Commercial Rd, Darwen BB3 0FJ - United Kingdom
Tel. : (+44) 0844 800 2788 - Fax : (+44) 0844 800 2789 - E-mail : sales@prevost-ltd.co.uk - www.prevost.eu International = PREVOST SAS - - C.S. 90208 - 74942 ANNECY-LE-VIEUX CEDEX - France Tel. : +33 (4)50 64 04 45 - Fax : +33 (0)4 50 64 00 10 - E-mail : sales@prevost.eu- www.prevost.eu

This document is non-contractual. PREVOST reserves the right to modify the features of its range without prior notice.