TCCPS RING AND SLIT STRIPPER INSTRUCTIONS

FOR SLIT STRIPPING

Step 1. Change the V cutting base to the desired fiber size.





Step 2. If necessary, adjust the slitting blade height.



Step 3. Insert the fiber cable into the groove and pull the cable to slit as needed.




FOR RING STRIPPING

Step 1. If necessary, adjust the stripping blade height using the top knob.



Step 2. Insert the fiber optic cable into the desired groove and spin the TCCPS around the cable. Dress cable as needed.





TCCPS SPECIFICATIONS

Length: 2.87" (72.9mm)
Weight: 0.05lbs (22g)
Material Body: ABS
Blade: SK5

1. Slit stripping Ø1.2~3.2mm fiber optic
2. Slit stripping Ø3.2~6.4mm fiber optic
3. Rotary stripping Ø3.2~6.4mm fiber optic
4. Rotary stripping Ø1.2~3.2mm fiber optic

REPLACEMENT BLADE SETS
TCCPS-RING-2
TCCPS-SLIT-2

1390 Aspen Way Vista, CA • 92081
Latin America Phone : 1.760.510.0558 | EMEA Phone: +44 (0) 1633 927 050
©2021 Tempo Communications Inc. • An ISO 9001 Company
TempoCom.com | tel 800.642.2155 | sales@tempocom.com

Follow us on Social Media
@TempoComms