Date: 25/01/2024

732.51.100 25 mbar 2 x G 1/4 female

Differential pressure gauge

Item number:	9082794
Quantity:	1 pcs.
Order code:	732.51-ZZ E-8MG125Z-AA-UDZZZA ZZ-ZZZZ 7A 3ECZ3DFHZ-IZZZZZZ12ZZZ
Overview:	732.51.100 25 mbar 2 x G 1/4 female Connector location: lower mount case: with pressure blowout disk max. static pressure: 2,5 bar Overpressure safety: 2,5 bar class 1.6 venting of pressure chamber Ingress protection: IP 54 Window: laminated safety glass Permissible ambient temperature: -20...+60 °C Permissible medium temperature: -20...+100 °C Pressure Gauge Standard: International (standard Europe) *WIKA* with Serial number
Details:	Differential pressure gauge Process industry series All wellded construction Model: 732.51 Specifications according to data sheet: PM 07.05 Case: stainless steel Bezel ring: stainless steel Movement: stainless steel Case filling: without Nominal size: 100 mm Scale range: 0...25 mbar Process connection: 2 x G 1/4 female Connector location: lower mount Venting of pressure chamber/flushing connection: venting of pressure chamber Permissible ambient temperature: -20...+60 °C Permissible medium temperature: -20...+100 °C Accuracy class: class 1.6 max. static pressure: 2,5 bar Overpressure safety: 2,5 bar Case material: Stainless steel 1.4301 Case surface: bare Ingress protection: IP 54 Pressure Gauge Standard: International (standard Europe) Manufacturer logo: *WIKA*

© 2024 - WIKA Instruments s.a.r.l.

Serial number: with Serial number
Window: laminated safety glass
case: with pressure blowout disk

© 2024 - WIKA Instruments s.a.r.l.