Specifications

Eaton 199408

Catalog Number: 199408

Eaton DC1 Variable frequency drive, 230 V AC, 1-phase, 10.5 A, 2.2 kW, IP66/NEMA 4X, Radio interference suppression filter, Brake chopper, 7-digital display assembly, Local controls, Additional PCB protection, UV resistant, FS2



General specifications

Product Name
Eaton DC1 Variable frequency drive

Catalog Number
199408

EAN
4015081977970

Product Length/Depth
182 mm

Product Height
257 mm

Product Width
188 mm

Product Weight
3.5 kg

Certifications
RCM
Certified by UL for use in Canada
UL Listed
UL report applies to both US and Canada
CE marking
UL File No.: E172143
UL Category Control No.: NMMS, NMMS7
IEC/EN61800-5
CUL
CE
IEC/EN 61800-3
UL 508C
RoHS, ISO 9001
IEC/EN 61800-5-1
IEC/EN 61800-2

Powering Business Worldwide

UkrSEPRO

CSA-C22.2 No. 14

U

EAC

Features & Functions

Features

Parameterization: drivesConnect

Parameterization: drivesConnect mobile (App)

Parameterization: Fieldbus

Parameterization: Keypad

Fitted with:

Brake chopper

IGBT inverter

UV resistance

7-digital display assembly

Radio interference suppression filter

Additional PCB protection

Control unit

Local controls

PC connection

Breaking resistance

Internal DC link

Functions

4-quadrant operation possible

Catalog Notes

Environmental class: 3C3, 3S3

Overload cycle for 60 s every 600 s

For normal internally and externally ventilated four-pole three-phase asynchronous motors with 1500 rpm at 50 Hz and 1800 rpm at 60 Hz

General

Cable length

C1 ≤ 1 m, maximum motor cable length

300 m, unscreened, with motor choke, maximum permissible, Motor feeder

100 m, screened, maximum permissible cable length

150 m, unscreened, maximum permissible cable length

C2 ≤ 5 m, maximum motor cable length

200 m, screened, with motor choke, maximum permissible cable length

C3 ≤ 25 m, maximum motor cable length

Communication interface

Modbus RTU, built in

SmartWire-DT, optional

OP-Bus (RS485), built in

CANopen®, built in

Connection to SmartWire-DT

No

Degree of protection

IP66

Climatic environmental conditions

Altitude

Above 1000 m with 1 % derating per 100 m

Max. 4000 m

Ambient operating temperature - min

-20 °C

Ambient operating temperature - max

40 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

60 °C

Climatic proofing

< 95 average relative humidity (RH), no condensation, no corrosion

Main circuit

NEMA 4X

Electromagnetic compatibility

1st and 2nd environments (according to EN 61800-3)

Frame size

FS2

Mounting position

Vertical

Product category

Variable frequency drives

Protection

Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)

Protocol

EtherNet/IP
Other bus systems
CAN
MODBUS

Radio interference class

C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.
C1: for conducted emissions only
Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments

Suitable for

Branch circuits, (UL/CSA)

Efficiency

97 % (η)

Heat dissipation capacity Pdiss

0 W

Input current ILN at 150% overload

19.2 A

Leakage current at ground IPE - max

4.8 mA

Mains switch-on frequency

Maximum of one time every 30 seconds

Mains voltage - min

200 V

Mains voltage - max

240 V

Operating mode

Speed control with slip compensation
Synchronous reluctance motors
PM motors
U/f control
Sensorless vector control (SLV)
BLDC motors

Output frequency - min

0 Hz

Output frequency - max

500 Hz

Output voltage (U2)

230 V AC, 3-phase
240 V AC, 3-phase

Overload current IL at 150% overload

15.75 A

Rated control supply voltage

10 V DC (Us, max. 10 mA)

Rated frequency - min

48 Hz

Rated frequency - max

62 Hz

Rated operational current (Ie)

10.5 A at 150% overload (at an operating frequency of 6 kHz and an ambient air temperature of +40 °C)

Rated operational voltage

240 V AC, 1-phase

230 V AC, 1-phase

Resolution

0.1 Hz (Frequency resolution, setpoint value)

Short-circuit protection rating

25 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring

Starting current - max

175 % IH

Supply frequency

50/60 Hz

Switching frequency

8 kHz, 4 - 32 kHz adjustable (audible), fPWM, Power section, Main circuit

System configuration type

AC supply systems with earthed center point

Voltage rating - max

240 V

Motor rating

Assigned motor current IM at 110/120 V, 60 Hz, 150% overload

9.6 A

Assigned motor current IM at 115 V, 50 Hz, 150% overload

8.7 A

Assigned motor current IM at 220 - 240 V, 60 Hz, 150% overload

9.6 A

Assigned motor current IM at 230 V, 50 Hz, 150% overload

8.7 A

Assigned motor current IM at 400 V, 50 Hz, 150% overload

8.7 A

Assigned motor current IM at 440 - 480 V, 60 Hz, 150% overload

9.6 A

Assigned motor power at 115/120 V, 60 Hz, 1-phase

3 HP

Assigned motor power at 230/240 V, 60 Hz, 1-phase

3 HP

Assigned motor power at 460/480 V, 60 Hz

3 HP

Assigned motor power at 460/480 V, 60 Hz, 3-phase

3 HP

Apparent power

Apparent power at 230 V

4.18 kVA

Apparent power at 240 V

4.36 kVA

Braking function

Braking resistance

50 Ω

Braking torque

Max. 30 % MN, Standard - Main circuit

Max. 100 % of rated operational current Ie with external braking resistor - Main circuit

Max. 100 % of rated operational current Ie, variable, DC - Main circuit

Switch-on threshold for the braking transistor

390 VDC

Control circuit

Number of inputs (analog)

Design verification

Heat dissipation capacity Pdiss

2 (parameterizable, 0 - 10 V DC, 0/4 - 20 mA)

Number of inputs (digital)

4 (parameterizable, 10 - 30 V DC)

Number of outputs (analog)

1

Number of outputs (digital)

1

Number of relay outputs

1 (parameterizable, N/O, 6 A (250 V, AC-1) / 5 A (30 V, DC-1))

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Application notes

Access to Parameter Levels 2 + 3 Parameter Lock - Load Default

Starting, Stopping and Operation

Electromagnetic compatibility (EMC)

How does the internal motor protection work?

Fire Mode

Update DX-COM-STICK3

Connecting drives to generator supplies

Operating Single Phase Motors

Set Point Setting

DX-COM-STICK3_Connection

The OP System Bus - Parameterizing - Control

Motor data - Motor Protection - V/f curves Slip Compensation

Conformal Coating

Dependency of the output current on switching frequency and ambient temperature

Operating Permanent Magnet and Brushless DC Motors

Low Temperature Applications

I/O Configuration

PI controller

Brochures

eaton-powerxl-variable-frequency-drives-dc1-da1-brochure-br040001en-en-us.pdf

DA-SW-drivesConnect

Catalogs

Product Range Catalog Drives Engineering

Declarations of conformity

DA-DC-00003964.pdf

DA-DC-00004184.pdf

DA-DC-00004555.pdf

DA-DC-00004552.pdf

Drawings

eaton-frequency-inverter-dc1-dimensions-003.eps

Installation instructions

eaton-powerxl-dc1-ip66-instruction-leaflet-il040059zu.pdf

Installation videos

Video PowerXL DA1

PowerXL Variable Frequency Drives DC1 and DA1 - EN

Manuals and user guides

MN040018_EN

MN040022_EN

eaton-canopen-communication-manual-for-variable-frequency-drives-variable-speed-starters-da1-db1-dc1-de11-mn040019-en-us.pdf

MN040003_EN

MN040059_EN

mCAD model

e3_s2_ip66_mit_bedienelementen.stp

e3_s2_ip66_mit_bedienelementen.dwg

Multimedia

Looking for variable frequency drives DC1 and DA1 which can be used in harsh environments?

Product notifications

eaton-drives-ecodesign-directive-mz040046en-en.pdf

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia